

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 November 2005 (24.11.2005)

PCT

(10) International Publication Number
WO 2005/110244 A1

(51) International Patent Classification⁷: **A61B 17/04**

(21) International Application Number:
PCT/US2005/015765

(22) International Filing Date: 6 May 2005 (06.05.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/841,411 7 May 2004 (07.05.2004) US
10/840,951 7 May 2004 (07.05.2004) US
10/840,950 7 May 2004 (07.05.2004) US
10/841,245 7 May 2004 (07.05.2004) US
10/869,472 15 June 2004 (15.06.2004) US
11/036,866 14 January 2005 (14.01.2005) US

(71) Applicant (for all designated States except US): USGI
MEDICAL INC. [US/US]; 1140 Calle Cordillera, San
Clemente, CA 92673 (US).

(72) Inventors: and

(75) Inventors/Applicants (for US only): SAADAT, Valid
[US/US]; 12679 Kane Drive, Saratoga, CA 95070 (US).
MAAHS, Tracy, D. [US/US]; 11 Paseo Simpatico, Ran-
cho Santa Margarita, CA 92688 (US). EWERS, Richard,

C. [US/US]; 1437 West Malvern, Fullerton, CA 92833
(US). ELMER, Marvin, C. [US/US]; 68 Tierra Segura,
Rancho Santa Margarita, CA 92688 (US). FLORES,
Jesus [US/US]; 319 Chochise Road, Perris, CA 92570
(US). KHAIRKHAHAN, Alex [US/US]; 1105 Lincoln
Avenue, Palo Alto, CA 94301 (US). PEH, Ruey-Feng
[SG/US]; 555 East El Camino Real #707, Sunnyvale, CA
94087 (US). LAM, Cong, C. [US/US]; 74 Stanford Court,
Irvine, CA 92612 (US).


(74) Agents: HESLIN, James, M. et al.; Townsend and
Townsend and Crew LLP, Two Embarcadero Center, 8th
Floor, San Francisco, California 94111-3834 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM,
PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU,
ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SI, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: APPARATUS AND METHODS FOR POSITIONING AND SECURING ANCHORS



(57) Abstract: Apparatus and methods for positioning and securing anchors are disclosed herein. The anchors are adapted to be delivered and implanted into or upon tissue, particularly tissue within the gastrointestinal system of a patient. The anchor is adapted to slide uni-directionally over suture such that a tissue plication may be cinched between anchors. A locking mechanism either within the anchor itself or positioned proximally of the anchor may allow for the uni-directional translation while enabling the anchor to be locked onto the suture if the anchor is pulled, pushed, or otherwise urged in the opposite direction along the suture. This uni-directional anchor locking mechanism facilitates the cinching of the tissue plication between the anchors and it may be utilized in one or several anchors in cinching a tissue fold.

WO 2005/110244 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

APPARATUS AND METHODS FOR POSITIONING AND SECURING ANCHORS

CROSS-REFERENCES TO RELATED APPLICATIONS

5 [0001] This is a continuation-in-part application of U.S. Pat. App. Serial Nos. 10/840,950 (Attorney docket no. 021496-000900 US); 10/841,245 (Attorney docket no. 021496-001000 US); 10/840,951 (Attorney docket no. 021496-001100 US); and 10/841,411 (Attorney docket no. 021496-001200 US), each of which was filed May 7, 2004. This present application is also a continuation-in-part of U.S. Pat. App. Serial Nos. 10/869,472 (Attorney docket no. 10 021496-000910 US), filed on June 15, 2004 and 11/036,866 (Attorney docket no. 021496-000940 US), filed January 14, 2005, each of which is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

[0002] Field of the Invention. The present invention relates to apparatus and methods for 15 positioning and securing anchors within tissue. More particularly, the present invention relates to apparatus and methods for positioning and securing anchors within folds of tissue within a body.

[0003] Morbid obesity is a serious medical condition pervasive in the United States and other countries. Its complications include hypertension, diabetes, coronary artery disease, 20 stroke, congestive heart failure, multiple orthopedic problems and pulmonary insufficiency with markedly decreased life expectancy.

[0004] A number of surgical techniques have been developed to treat morbid obesity, e.g., bypassing an absorptive surface of the small intestine, or reducing the stomach size. However, many conventional surgical procedures may present numerous life-threatening 25 post-operative complications, and may cause atypical diarrhea, electrolytic imbalance, unpredictable weight loss and reflux of nutritious chyme proximal to the site of the anastomosis.

[0005] Furthermore, the sutures or staples that are often used in these surgical procedures typically require extensive training by the clinician to achieve competent use, and may 30 concentrate significant force over a small surface area of the tissue, thereby potentially

causing the suture or staple to tear through the tissue. Many of the surgical procedures require regions of tissue within the body to be approximated towards one another and reliably secured. The gastrointestinal lumen includes four tissue layers, wherein the mucosa layer is the inner-most tissue layer followed by connective tissue, the muscularis layer and the serosa layer.

[0006] One problem with conventional gastrointestinal reduction systems is that the anchors (or staples) should engage at least the muscularis tissue layer in order to provide a proper foundation. In other words, the mucosa and connective tissue layers typically are not strong enough to sustain the tensile loads imposed by normal movement of the stomach wall during ingestion and processing of food. In particular, these layers tend to stretch elastically rather than firmly hold the anchors (or staples) in position, and accordingly, the more rigid muscularis and/or serosa layer should ideally be engaged. This problem of capturing the muscularis or serosa layers becomes particularly acute where it is desired to place an anchor or other apparatus transesophageally rather than intraoperatively, since care must be taken in piercing the tough stomach wall not to inadvertently puncture adjacent tissue or organs.

[0007] One conventional method for securing anchors within a body lumen to the tissue is to utilize sewing devices to suture the stomach wall into folds. This procedure typically involves advancing a sewing instrument through the working channel of an endoscope and into the stomach and against the stomach wall tissue. The contacted tissue is then typically drawn into the sewing instrument where one or more sutures or tags are implanted to hold the suctioned tissue in a folded condition known as a plication. Another method involves manually creating sutures for securing the plication.

[0008] One of the problems associated with these types of procedures is the time and number of intubations needed to perform the various procedures endoscopically. Another problem is the time required to complete a plication from the surrounding tissue with the body lumen. In the period of time that a patient is anesthetized, procedures such as for the treatment of morbid obesity or for GERD must be performed to completion. Accordingly, the placement and securement of the tissue plication should ideally be relatively quick and performed with a minimal level of confidence.

[0009] Another problem with conventional methods involves ensuring that the staple, knotted suture, or clip is secured tightly against the tissue and that the newly created plication will not relax under any slack which may be created by slipping staples, knots, or clips.

Other conventional tissue securement devices such as suture anchors, twist ties, crimps, etc. are also often used to prevent sutures from slipping through tissue. However, many of these types of devices are typically large and unsuitable for low-profile delivery through the body, e.g., transesophageally.

- 5 [0010] Moreover, when grasping or clamping onto or upon the layers of tissue with conventional anchors, sutures, staples, clips, etc., many of these devices are configured to be placed only after the tissue has been plicated and not during the actual plication procedure.

BRIEF SUMMARY OF THE INVENTION

- 10 [0011] In securing plications which may be created within a body lumen of a patient, various methods and devices may be implemented. Generally, any number of conventional methods may be utilized for initially creating the plication. One method in particular may involve creating a plication through which a tissue anchor may be disposed within or through. A distal tip of a tissue plication apparatus may engage or grasp the tissue and move the engaged tissue to a proximal position relative to the tip of the device, thereby providing a
- 15 substantially uniform plication of predetermined size. Examples of tools and methods which are particularly suited for delivering the anchoring and securement devices may be seen in further detail in co-pending U.S. Pat. App. Serial No. 10/735,030 filed December 12, 2003, which is incorporated herein by reference in its entirety.

- 20 [0012] In securing these plications, various tissue anchors may be utilized for securing the plications in their configured folds. For example, a plication (or plications) may be secured via a length or lengths of suture extending through the plication and between a distally-positioned tissue anchor located on a distal side of the plication and a proximally-positioned tissue anchor located on a proximal side of the plication. Examples of anchors which may be utilized are disclosed in co-pending U.S. Pat. App. Serial No. 10/612,170, filed July 1, 2003,
- 25 which is incorporated herein by reference in its entirety.

- [0013] Generally, in securing a tissue plication, a proximally and/or distally located tissue anchor is preferably configured to slide along the connecting suture in a uni-directional manner. For instance, if the proximal anchor is to be slid along the suture, it is preferably configured to translate over the suture such that the tissue plication is cinched between the
- 30 anchors. In this example, the proximal anchor is preferably configured to utilize a locking mechanism which allows for the free uni-directional translation of the suture therethrough

while enabling the anchor to be locked onto the suture if the anchor is pulled, pushed, or otherwise urged in the opposite direction along the suture. This uni-directional anchor locking mechanism facilitates the cinching of the tissue plication between the anchors and it may be utilized in one or several of the anchors in cinching a tissue fold.

5 [0014] Moreover, the types of anchors utilized for the securement of tissue plications are not intended to be limiting. For instance, many of the anchor locking or cinching mechanisms may be utilized with, e.g., "T"-type anchors as well as with reconfigurable "basket"-type anchors, which generally comprise a number of configurable struts or legs extending between at least two collars or support members. Other variations of these or other
10 types of anchors are also contemplated for use in an anchor locking or cinching assembly.

[0015] For instance, linear anchors, i.e., elongate anchors which are configured to fold or become compressed into a bowed or expanded configuration, may also be utilized. Such anchors may be configured in a variety of different configurations, such as flattened ribbon or wire, having one or more openings along its length through which a length of suture may be
15 routed. Generally, a linear-type anchor for placement against a tissue surface may comprise an elongate member having a proximal end, a distal end, and a length therebetween defining a plurality of holes, a length of suture for passage through at least one of the holes, and wherein the elongate member is adapted to be reconfigured from a straightened configuration to an expanded anchoring configuration when the elongate member is compressed
20 longitudinally. In utilizing such a linear-type anchor, one method of positioning the anchor against the tissue surface may generally comprise positioning an elongate member in a straightened configuration against the tissue surface, the elongate member having a proximal end, a distal end, and a length therebetween, and compressing the elongate member longitudinally such that the elongate member reconfigures to an expanded anchoring
25 configuration against the tissue surface.

[0016] Furthermore, a single type of anchor may be used exclusively in an anchor locking or cinching assembly; alternatively, a combination of different anchor types each utilizing different anchor locking or cinching mechanisms may be used in a single assembly. Furthermore, the different types of cinching or locking mechanisms are not intended to be
30 limited to any of the particular variations shown and described below but may be utilized in any combinations or varying types of anchors as practicable.

[0017] The suture itself may be modified or altered to integrate features or protrusions along its length or a specified portion of its length. Such features may be defined uniformly at regular intervals along the length of suture or intermittently, depending upon the desired locking or cinching effects. Furthermore, the suture may be made from metals such as Nitinol, stainless steels, Titanium, etc., provided that they are formed suitably thin and flexible. Using metallic sutures with the anchoring mechanisms may decrease any possibilities of suture failure and it may also provide a suture better able to withstand the acidic and basic environment of the gastrointestinal system. Also, it may enhance imaging of the suture and anchor assembly if examined under imaging systems. Sutures incorporating the use of features or protrusions along its length as well as sutures fabricated from metallic materials or any other conventional suture type may be utilized with any of the locking or cinching mechanisms described below in various combinations, if so desired.

[0018] One variation for utilizing a locking mechanism which allows for free uni-directional translation of the suture through the anchor may include blocks or members which are adapted to slide within or upon an anchor to lock the suture. These blocks or members may include tapered edges which act to cleat the suture depending upon the direction the anchor is translated relative to the suture. Moreover, these blocks may be biased or urged to restrict the movement of the suture using a variety of biasing elements, such as springs, etc. In addition to blocks, one or several locking tabs which are levered to allow uni-directional travel of the suture through an anchor may also be utilized.

[0019] Aside from the use of mechanical locking features integrated within or with the anchor bodies, locking mechanisms may also utilize a variety of knotting techniques. Conventional knots, which are typically tied by the practitioner either within the body or outside the body and advanced over the suture length, may be utilized for locking the anchor in place relative to the tissue fold and opposing anchor; however, self-locking knots which enable the uni-directional travel of an anchor body relative to the suture and tissue are desirable. Accordingly, many different types of self-locking knots may be advanced with the anchor over the suture such that translation along a distal direction is possible yet reverse translation of the anchor is inhibited.

[0020] Various anchor cinching or locking mechanisms utilizing friction as a primary source for locking may also be implemented. For instance, locking pins may be urged or pushed into a frictional interference fit with portions or areas of the suture against the anchor

or portions of the anchor. The use of such pins may effectively wedge the suture and thereby prevent further movement of the anchor along the suture length. In addition to pins, locking collars or collets may also be used to cinch or lock the suture.

5 [0021] In addition to friction-based locking and cinching mechanisms utilizable in tissue anchors, other mechanisms which create tortuous paths for the suture within or through the anchors may also be utilized for creating uni-directional locking. One cinching variation may utilize a pulley or pin contained within the anchor over which a portion of the suture may travel. The looped suture may then be routed proximally and secured with a slip knot. As tension is applied to the suture, the slip knot may prevent the further movement of the anchor
10 relative to the suture.

[0022] Another variation on utilizing tortuous paths may comprise collars which are independent from or integrally formed with the anchors. Such cinching collars may generally be formed into tubular structures having obstructions or interference elements disposed or formed within the collar lumen where the obstructions may, for example, be formed from
15 portions of the cinching collar itself. These obstructions may be adapted to form upon releasing of a constraining force when the anchor is to be locked into position. Alternatively, the interference elements or obstructions may comprise separate elements disposed within the collar lumen, such as one or more balls, spheres, etc. These obstructions or elements may be used to form a tortuous path through which the suture may be routed to lock the suture
20 within.

[0023] Moreover, locking collars which form tortuous paths may be adapted to reconfigure themselves from a constrained delivery configuration to a deployed locking configuration when the anchor is to be cinched or locked into position relative to the tissue and suture. The locking collars may be configured to take various configurations, such as a proximally
25 extending "S"-type, or other types, configuration.

[0024] Other cinching and locking mechanisms which utilize mechanical clamping or crimping to achieve locking of the suture within or through the anchors may also be used to facilitate uni-directional locking. For instance, a simple mechanical crimp may be fastened upon the suture proximally of the anchor to prevent the reverse motion of the anchor. The
30 crimp may be a simple tubular member or it may be integrally formed onto a proximal portion of the anchor body itself.

[0025] Aside from the crimping mechanisms described above, additional measures may be optionally implemented to facilitate the cinching or locking of an anchor. Other measures may also be taken to inhibit any damage from occurring to the suture routed through an anchor. For instance, to ensure that the integrity of the suture is maintained in the presence of metallic basket anchors and to ensure that the suture is not subjected to any nicks or cuts, the portion of the suture passing through basket anchor may be encased in a protective sleeve made, e.g., from polypropylene, PTFE, etc.

[0026] Another measure which may optionally be implemented are cinching or locking mechanisms which take advantage of any cold-flow effects of an engaged portion of suture by the tissue anchor. For instance, if a portion of the suture is wedged against the collar of an anchor or cinching member to lock the anchor, the portion of the collar may have multiple holes defined over its surface to allow for portions of the engaged suture to cold-flow at least partially into or through the holes to enhance the locking effects.

[0027] Alternatively, the collar may be formed with an electrically conductive inner sleeve surrounded by an outer sleeve capable of flowing at least partially when heated. The inner sleeve may have a number of holes defined over its surface such that when the outer sleeve is heated, either by inductive heating or any other method, the outer sleeve material may flow through the holes and into contact with the suture passing therethrough. This contact may also enhance the locking effects of the collar.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] Fig. 1A shows a side view of one variation of a tissue plication apparatus which may be used to create tissue plications and to deliver cinching or locking anchors into the tissue.

[0029] Figs. 1B and 1C show detail side and perspective views, respectively, of the tissue manipulation assembly of the device of Fig. 1A.

[0030] Figs. 2A to 2D show an example of a tissue plication procedure for the delivery and placement of tissue anchors.

[0031] Figs. 3A to 3G show detail cross-sectional views of an anchor delivery assembly in proximity to a tissue plication and an example of delivering the tissue anchors on distal and proximal sides of the plication.

[0032] Figs. 4A and 4B show side and end views, respectively, of one anchor variation which is illustrated in the form of a T-type anchor utilizing locking blocks or members for cinching and locking the suture.

5 [0033] Fig. 5 shows a side view of another cinching anchor variation utilizing locking blocks or members.

[0034] Fig. 6 shows yet another side view of a cinching anchor variation utilizing locking blocks or members.

[0035] Fig. 7 shows a perspective view of another locking anchor variation in which the anchor body defines an opening having a tapered or grooved portion.

10 [0036] Figs. 8A and 8B show cross-sectional side and top views, respectively, of another locking anchor variation utilizing a through-hole passage or opening and uni-directional levers or pivots through which the suture may pass.

[0037] Fig. 8C shows a cross-sectional side view of an anchor body in combination with a modified suture having integrated features or protrusions defined along its length.

15 [0038] Figs. 9A and 9B show cross-sectional views of locking anchor variations having biased locking members in combination with a knotted suture.

[0039] Fig. 9C shows another modification of the suture which may be coated with a metallic covering or slid within a sleeve.

20 [0040] Fig. 10 shows a cross-sectional side view of an anchor assembly which utilizes a choke-type loop for cinching the anchors uni-directionally towards one another.

[0041] Fig. 11A shows a perspective view of another anchor assembly utilizing a slip knot at the proximal anchor.

25 [0042] Figs. 11B and 11C show top and cross-sectional side views, respectively, of an anchor which may optionally define grooves or channels extending at least partially therein to facilitate the cinching or wedging of the sutures within the grooves.

[0043] Figs. 12A to 12G show examples of anchor assemblies utilizing various slip knots and looped sections which provide uni-directional travel for the anchors over the sutures.

[0044] Fig. 13A shows a cross-sectional side view of an anchor delivery system delivering a basket-type anchor into or through a tissue plication.

[0045] Fig. 13B shows a cross-sectional side view of multiple tissue plications which may be cinched towards one another and basket anchors as being deliverable through one or both tissue plications.

5 [0046] Figs. 14A and 14B show cross-sectional side views of an anchor cinching assembly utilizing a cinching collar or collet which may be wedged into an anchor collar for clamping upon the suture.

[0047] Figs. 15A and 15C show cross-sectional side views of another anchor cinching assembly utilizing a pin for wedging against a portion of the suture.

10 [0048] Figs. 15B and 15D show end views of the assembly of Figs. 15A and 15C, respectively.

[0049] Fig. 15E shows a perspective view of another cinching variation utilizing one or more tapered pins or blocks slidably disposed within a tapered channel defined in a proximal collar of the anchor.

[0050] Fig. 15F shows a perspective view of the tapered pins from Fig. 15E.

15 [0051] Figs. 15G and 15H show cross-sectional side views of an alternative cinching assembly having a retractable pin in an engaged and disengaged configuration, respectively.

[0052] Figs. 16A and 16B show cross-sectional side views of another variation of a cinching assembly having a rotatable cinching collar.

20 [0053] Figs. 17A and 17B show cross-sectional side views of another cinching assembly having a retaining tube for providing a counterforce to stabilize the assembly during cinching or locking.

[0054] Figs. 18A and 18B show cross-sectional side views of another cinching assembly having one or several biasing members or cinching tabs.

25 [0055] Figs. 18C and 18D show end and perspective views, respectively, of a suture release member which may be used with the assembly of Figs. 18A and 18B.

[0056] Figs. 19A and 19B show cross-sectional side views of another variation of a cinching assembly utilizing a deformable cinching member positioned within the anchor and distally of the anchor collar.

[0057] Fig. 20A shows a cross-sectional side view of another cinching assembly utilizing a pivoting cinching member configured to lock against the suture.

[0058] Figs. 20B, 20C, and 20D show end and cross-sectional side views, respectively, of the pivoting member positioned within the anchor collar.

- 5 [0059] Figs. 20E and 20F show cross-sectional side and perspective views, respectively, of another cinching assembly having a pivoting cinching member positioned proximally of the anchor collar.

[0060] Figs. 21A and 21B show cross-sectional side views of another cinching assembly configured to cinch or lock the suture with a tapered collar.

- 10 [0061] Fig. 22A shows a cross-sectional side view of another cinching assembly utilizing a looped suture and a slip knot for cinching the anchor over the suture.

[0062] Figs. 22B and 22C show cross-sectional side and detail views, respectively, of another cinching assembly which may be utilized with a portion of suture wrapped or looped about a pin which enables uni-directional travel of the anchor relative to the suture

- 15 [0063] Figs. 22D and 22E show cross-sectional side and detail views, respectively, of another cinching assembly utilizing looped suture wedged within the anchor collar.

[0064] Fig. 23 shows a cross-sectional side view of a cinching assembly variation utilizing a number of pulleys to create the cinching effect.

- 20 [0065] Fig. 24A shows a cross-sectional side view of another cinching assembly variation in which a cinching sleeve may be used to create a tortuous path for the suture.

[0066] Figs. 24B and 24C show cross-sectional side views of another cinching assembly variation having a tubular structure, with and without retaining arms, respectively, positioned within the anchor collar through which the suture may pass uni-directionally.

- 25 [0067] Fig. 24D shows a perspective view of one variation of the tubular structure of Fig. 24C with retaining arms.

[0068] Figs. 25A and 25B show cross-sectional side views of another cinching assembly variation in which a cinching collar, which may be independent of the anchor or formed integrally with the anchor, respectively, may have a tortuous path formed within the collar.

[0069] Fig. 25C shows a perspective view of the collar of Fig. 25A in its unobstructed configuration with a constraining sleeve which may be positioned within the collar.

5 [0070] Figs. 26A and 26B show cross-sectional side views of another cinching assembly variation utilizing one or several pivoting levers which allow uni-directional travel of the suture therethrough.

[0071] Figs. 26C and 26D show alternative end views of the assembly of Fig. 26A in which the lever may be configured to prevent over cinching onto the suture.

[0072] Figs. 26E to 26G show cross-sectional side views of alternative cinching assemblies in which the levers may be variously configured to create the tortuous path.

10 [0073] Figs. 27A and 27B show side views of another cinching assembly variation in a delivery profile and a reconfigured profile, respectively, which utilizes a crimp which may be self-forming.

[0074] Figs. 28A and 28B show cross-sectional side views of another cinching assembly variation utilizing either two cinching collars or a single integral cinching collar, respectively.

15 [0075] Fig. 28C shows a cross-sectional side view of the cinching collar of Fig. 28A in one configuration for cinching the suture.

[0076] Figs. 28D and 28E show perspective views of the cinching collar of Fig. 28A in a delivery profile and a reconfigured profile.

20 [0077] Fig. 28F shows a cross-sectional side view of another variation for a cinching configuration of the cinching collar of Fig. 28B.

[0078] Figs. 28G and 28H show cross-sectional side views of another cinching assembly variation in a delivery profile and reconfigured profile, respectively, in which an elongate cinching member may reconfigure itself to create a tortuous path for the suture.

25 [0079] Figs. 29A and 29B show cross-sectional side views of another cinching assembly variation utilizing a mechanical crimp.

[0080] Figs. 30A and 30B show cross-sectional side views of another cinching assembly variation in which a mechanical crimp may be utilized on the proximal collar of the anchor body.

[0081] Fig. 31A shows a cross-sectional side view of a variation of a tool assembly which may be adapted to apply a mechanical crimping force upon a crimping collar.

[0082] Figs. 31B to 31D show side, end, and perspective views, respectively, of a variation on a crimping collar which may be utilized as a separate crimping sleeve or as part of the anchor collar.

[0083] Figs. 32A and 32B show cross-sectional side and perspective views, respectively, of an alternative crimping tool.

[0084] Figs. 33A and 33B show perspective and end views, respectively, of a representative basket anchor having a protective sleeve encasing the suture disposed within the anchor.

[0085] Figs. 34A and 34B show cross-sectional side and perspective views, respectively, of a cinching collar defining a plurality of holes through the surface of the collar for enhancing the locking effects with the suture.

[0086] Fig. 35A shows a cross-sectional side view of a cinching assembly variation which may utilize inductive heating to partially melt a portion of an outer sleeve into contact with the suture to enhance the anchor locking effects.

[0087] Figs. 35B and 35C show perspective assembly and exploded views, respectively, of an electrically conductive inner sleeve contained within the outer sleeve.

[0088] Figs. 35D and 35E show perspective views of alternative inner sleeves which may be utilized with the assembly of Fig. 35A.

[0089] Figs. 36A and 36B show perspective views of variations of linear anchors generally comprised of elongate ribbon or flattened wire and defining one or more openings along their lengths.

[0090] Figs. 37A and 37B show the ribbon anchors of Figs. 36A and 36B, respectively, with lengths of suture routed through the openings.

[0091] Fig. 38 shows another variation of a ribbon anchor having alternating portions of the ribbon material between the openings notched out or removed.

[0092] Fig. 39 shows another variation of a ribbon anchor defining undulations such that an "S"-type ribbon pattern is formed.

[0093] Fig. 40A shows the ribbon anchor of Fig. 36A with biasing springs positioned along portions of the ribbon anchor with suture routed therethrough.

[0094] Fig. 40B shows another variation of the ribbon anchor of Fig. 40A having biased ribbon elements rather than springs.

5 [0095] Fig. 40C shows the ribbon anchor of Fig. 40A in a partially collapsed configuration.

[0096] Fig. 40D shows the ribbon anchor of Fig. 40B in a partially collapsed configuration.

[0097] Fig. 41 shows an alternative variation of the ribbon anchor comprised of a tubular member.

10 [0098] Fig. 42 shows a perspective view of another alternative variation of the ribbon anchor comprised of a tubular member having a partial cut-out along its length.

[0099] Fig. 43 shows a perspective view of yet another alternative variation of the ribbon anchor having multiple cut-outs along its length.

[0100] Fig. 44 shows a perspective view of yet another alternative having multiple individual lengths of elements encased (or at least partially encased) in a coating or covering.

15 [0101] Fig. 45 shows a perspective view of yet another alternative having one or more lengths of wire covered or coated.

[0102] Fig. 46 shows another variation in which a length of the ribbon anchor may have a non-uniform thickness.

20 [0103] Figs. 47A and 47B shows yet other variations in which a length of wire having eyelets or defining loops may be utilized to fold or flatten into an expanded pattern.

[0104] Fig. 48 shows another variation in which a wire or ribbon may be comprised of a shape memory alloy which is configured to form a tangled portion of the wire when unconstrained.

25 [0105] Figs. 49A and 49B show partial cross-sectional views of ribbon anchors in a flattened linear configuration becoming compressed into a collapsed and expanded configuration, respectively, against a fold of tissue.

[0106] Figs. 50A to 50F show top views of various bowed or expanded configurations of a ribbon anchor.

[0107] Figs. 51A and 51B are side-views, partially in section, of a cinching assembly comprising an interference element.

[0108] Figs. 52A-52C are, respectively, an isometric view, a sectional isometric view and a side-sectional view of the cinching assembly of Figs. 51.

- 5 [0109] Figs. 53A-53D are side-views, partially in section, of variations of the cinching assembly of Figs. 51 and 52.

DETAILED DESCRIPTION OF THE INVENTION

[0110] In order to first create the plication within a body lumen of a patient, various methods and devices may be implemented. The anchoring and securement devices may be
10 delivered and positioned via an endoscopic apparatus that engages a tissue wall of the gastrointestinal lumen, creates one or more tissue folds, and disposes one or more of the anchors through the tissue fold(s). The tissue anchor(s) may be disposed through the muscularis and/or serosa layers of the gastrointestinal lumen.

[0111] Generally, in creating a plication through which a tissue anchor may be disposed
15 within or through, a distal tip of a tissue plication apparatus may engage or grasp the tissue and move the engaged tissue to a proximal position relative to the tip of the device, thereby providing a substantially uniform plication of predetermined size.

[0112] Formation of a tissue fold may be accomplished using at least two tissue contact areas that are separated by a linear or curvilinear distance, wherein the separation distance
20 between the tissue contact points affects the length and/or depth of the fold. In operation, a tissue grabbing assembly engages or grasps the tissue wall in its normal state (i.e., non-folded and substantially flat), thus providing a first tissue contact area. The first tissue contact area then is moved to a position proximal of a second tissue contact area to form the tissue fold. The tissue anchor assembly then may be extended across the tissue fold at the second tissue
25 contact area. Optionally, a third tissue contact point may be established such that, upon formation of the tissue fold, the second and third tissue contact areas are disposed on opposing sides of the tissue fold, thereby providing backside stabilization during extension of the anchor assembly across the tissue fold from the second tissue contact area.

[0113] The first tissue contact area may be utilized to engage and then stretch or rotate the
30 tissue wall over the second tissue contact area to form the tissue fold. The tissue fold may then be articulated to a position where a portion of the tissue fold overlies the second tissue

contact area at an orientation that is substantially normal to the tissue fold. A tissue anchor may then be delivered across the tissue fold at or near the second tissue contact area. An apparatus in particular which is particularly suited to deliver the anchoring and securement devices described herein may be seen in further detail in co-pending U.S. Pat. App. Serial No. 10/735,030 filed December 12, 2003 and entitled "Apparatus And Methods For Forming And
5 10/735,030 filed December 12, 2003 and entitled "Apparatus And Methods For Forming And Securing Gastrointestinal Tissue Folds", which is incorporated herein by reference in its entirety.

[0114] An illustrative side view of a tissue plication assembly 10 which may be utilized with the tissue anchors described herein is shown in Fig. 1A. The plication assembly 10
10 generally comprises a catheter or tubular body 12 which may be configured to be sufficiently flexible for advancement into a body lumen, e.g., transorally, percutaneously, laparoscopically, etc. Tubular body 12 may be configured to be torqueable through various methods, e.g., utilizing a braided tubular construction, such that when handle 16 is manipulated and rotated by a practitioner from outside the body, the torquing force is
15 transmitted along body 12 such that the distal end of body 12 is rotated in a corresponding manner.

[0115] Tissue manipulation assembly 14 is located at the distal end of tubular body 12 and is generally used to contact and form the tissue plication, as mentioned above. Fig. 1B shows an illustrative detail side view of tissue manipulation assembly 14 which shows launch tube
20 18 extending from the distal end of body 12 and in-between the arms of upper extension member or bail 20. Launch tube 18 may define launch tube opening 24 and may be pivotally connected near or at its distal end via hinge or pivot 22 to the distal end of upper bail 20. Lower extension member or bail 26 may similarly extend from the distal end of body 12 in a longitudinal direction substantially parallel to upper bail 20. Upper bail 20 and lower bail 26
25 need not be completely parallel so long as an open space between upper bail 20 and lower bail 26 is sufficiently large enough to accommodate the drawing of several layers of tissue between the two members.

[0116] Upper bail 20 is shown in the figure as an open looped member and lower bail 26 is shown as a solid member; however, this is intended to be merely illustrative and either or
30 both members may be configured as looped or solid members. Tissue acquisition member 28 may be an elongate member, e.g., a wire, hypotube, etc., which terminates at a tissue grasper 30, in this example a helically-shaped member, configured to be reversibly rotatable for

advancement into the tissue for the purpose of grasping or acquiring a region of tissue to be formed into a plication. Tissue acquisition member 28 may extend distally from handle 16 through body 12 and distally between upper bail 20 and lower bail 26. Acquisition member 28 may also be translatable and rotatable within body 12 such that tissue grasper 30 is able to
5 translate longitudinally between upper bail 20 and lower bail 26. To support the longitudinal and rotational movement of acquisition member 28, an optional guide or sled 32 may be connected to upper 20 or lower bail 26 to freely slide thereon. Guide 32 may also be slidably connected to acquisition member 28 such that the longitudinal motion of acquisition member 28 is supported by guide 32.

10 [0117] An example of a tissue plication procedure is seen in Figs. 2A to 2D for delivering and placing a tissue anchor and is disclosed in further detail in co-pending U.S. Pat. App. Serial No. 10/735,030 filed December 12, 2003, which has been incorporated by reference above. Tissue manipulation assembly 14, as seen in Fig. 2A, may be advanced into a body lumen such as the stomach and positioned adjacent to a region of tissue wall 40 to be
15 plicated. During advancement, launch tube 18 may be configured in a delivery profile such that tube 18 is disposed within or between the arms of upper bail 20 to present a relatively small profile.

[0118] Once tissue manipulation assembly 14 has been desirably positioned relative to tissue wall 40, tissue acquisition member 30 may be advanced distally such that tissue
20 acquisition member 30 comes into contact with tissue wall 40 at acquisition location or point 42. As acquisition member 30 is distally advanced relative to body 12, guide 32, if utilized, may slide distally along with member 30 to aid in stabilizing the grasper. If a helically-shaped acquisition member 30 is utilized, as illustrated in Fig. 2B, it may be rotated from its proximal end at handle 16 and advanced distally until the tissue at point 42 has been firmly
25 engaged by acquisition member 30. This may require advancement of acquisition member 30 through the mucosal layer and at least into or through the underlying muscularis layer and preferably into or through the serosa layer.

[0119] The grasped tissue may then be pulled proximally between upper 20 and lower bails 26 via acquisition member 30 such that the acquired tissue is drawn into a tissue fold 44, as
30 seen in Fig. 2C. As acquisition member 30 is withdrawn proximally relative to body 12, guide 32 may also slide proximally to aid in stabilizing the device especially when drawing the tissue fold 44.

[0120] Once the tissue fold 44 has been formed, launch tube 18 may be advanced from its proximal end at handle 16 such that a portion 46 of launch tube 18, which extends distally from body 12, is forced to rotate at hinge or pivot 22 and reconfigure itself such portion 46 forms a curved or arcuate shape that positions launch tube opening 24 perpendicularly relative to a longitudinal axis of body 12 and/or bail members 20, 26. Launch tube 18, or at least portion 46 of launch tube 18, is preferably fabricated from a highly flexible material or it may be fabricated, e.g., from Nitinol tubing material which is adapted to flex, e.g., via circumferential slots, to permit bending. Alternatively, assembly 14 may be configured such that launch tube 18 is reconfigured simultaneously with the proximal withdrawal of acquisition member 30 and acquired tissue 44.

[0121] As discussed above, the tissue wall of a body lumen, such as the stomach, typically comprises an inner mucosal layer, connective tissue, the muscularis layer and the serosa layer. To obtain a durable purchase, e.g., in performing a stomach reduction procedure, the staples or anchors used to achieve reduction of the body lumen are preferably engaged at least through or at the muscularis tissue layer, and more preferably, the serosa layer. Advantageously, stretching of tissue fold 44 between bail members 20, 26 permits an anchor to be ejected through both the muscularis and serosa layers, thus enabling durable gastrointestinal tissue approximation.

[0122] As shown in Fig. 2D, once launch tube opening 24 has been desirably positioned relative to the tissue fold 44, needle assembly 48 may be advanced through launch tube 18 via manipulation from its proximal end at handle 16 to pierce preferably through a dual serosa layer through tissue fold 44. Needle assembly 48 is preferably a hollow tubular needle through which one or several tissue anchors may be delivered through and ejected from in securing the tissue fold 44, as further described below.

[0123] Because needle assembly 48 penetrates the tissue wall twice, it exits within the body lumen, thus reducing the potential for injury to surrounding organs. A detail cross-sectional view is shown in Fig. 3A of anchor delivery assembly 50 in proximity to tissue fold F. In this example, tissue fold F may comprise a plication of tissue created using the apparatus 10 described herein or any other tool configured to create such a tissue plication. Tissue fold F may be disposed within a gastrointestinal lumen, such as the stomach, where tissue wall W may define the outer or serosal layer of the stomach. Anchor delivery assembly may generally comprise launch tube 18 and needle assembly 48 slidably disposed within launch

tube lumen 52. Needle assembly 48 is generally comprised of needle 54, which is preferably a hollow needle having a tapered or sharpened distal end 66 to facilitate its travel into and/or through the tissue. Other parts of the assembly, such as upper and lower bail members 20, 26, respectively, and tissue acquisition member 28 have been omitted from these figures only
5 for clarity.

[0124] Once launch tube 18 has been desirably positioned with respect to tissue fold F, needle 54 may be urged or pushed into or through tissue fold F via needle pushrod or member 56 from its proximal end preferably located within handle 16. Needle 54 may define needle lumen 58 within which distal anchor 62 and/or proximal anchor 64 may be situated
10 during deployment and positioning of the assembly. A single suture or flexible element 70 (or multiple suture elements) may connect proximal anchor 64 and distal anchor 62 to one another. For instance, element 70 may comprise various materials such as monofilament, multifilament, or any other conventional suture material, elastic or elastomeric materials, e.g., rubber, etc.

15 [0125] Alternatively, metals which are biocompatible may also be utilized for suture materials. For instance, sutures may be made from metals such as Nitinol, stainless steels, Titanium, etc., provided that they are formed suitably thin and flexible. Using metallic sutures with the anchoring mechanisms described herein may additionally provide several benefits. For example, use of metallic suture material may decrease any possibilities of
20 suture failure due to inadvertent cutting or shearing of the suture, it may provide a suture better able to withstand the acidic and basic environment of the gastrointestinal system, and it may also enhance imaging of the suture and anchor assembly if examined under conventional imaging systems such as X-rays, fluoroscopes, MRI, etc. As used herein, suture 70 may encompass any of these materials or any other suitable material which is also biocompatible.

25 [0126] Needle 54 may optionally define needle slot 60 along its length to allow suture 70 to pass freely within and out of needle 54 when distal anchor 62 is ejected from needle lumen 58. Alternatively, rather than utilizing needle slot 60, needle 54 may define a solid structure with suture 70 being passed into needle lumen 58 via the distal opening of needle 54.

[0127] The proximal end of suture 70 may pass slidingly through proximal anchor 64 to
30 terminate in suture loop 74 via cinching knot 72. Suture loop 74 may be omitted and the proximal end of suture 70 may terminate proximally of the apparatus 10 within control handle 16, proximally of control handle 16, or at some point distally of control handle 16. In

this variation, suture loop 74 may be provided to allow for a grasping or hooking tool to temporarily hold suture loop 74 for facilitating the cinching of proximal 64 and distal 62 anchors towards one another for retaining a configuration of tissue fold F, as described in further detail below. Cinching knot 72 may also comprise a slidable knot which may be slid
5 distally along suture 70 to lock or hold against proximal anchor 64 once the tissue fold F and anchors 62, 64 have been desirably positioned and tensioned, as also described below in further detail.

[0128] After needle assembly 48 has been pushed distally out through launch tube opening 24 and penetrated into and/or through tissue fold F, as shown in Fig. 3B, anchor pushrod or
10 member 68 may be actuated also via its proximal end to eject distal anchor 62, as shown in Fig. 3C. Once distal anchor 62 has been ejected distally of tissue fold F, Fig. 3D shows how needle 54 may be retracted back through tissue fold F by either retracting needle 54 back within launch tube lumen 52 or by withdrawing the entire anchor delivery assembly 50 proximally relative to tissue fold F.

[0129] Fig. 3E shows that once needle 54 has been retracted, proximal anchor 64 may then be ejected from launch tube 18 on a proximal side of tissue fold F. With both anchors 62, 64 disposed externally of launch tube 18 and suture 70 connecting the two, proximal anchor 64 may be held against the distal end of launch tube 18 and urged into contact against tissue fold F, as shown in Figs. 3F and 3G, respectively. As proximal anchor 64 is urged against tissue
20 fold F, proximal anchor 64 or a portion of suture 70 may be configured to provide any number of directionally translatable locking mechanisms which provide for movement of an anchor along suture 70 in a first direction and preferably locks, inhibits, or prevents the reverse movement of the anchor back along suture 70. In other alternatives, the anchors may simply be delivered through various elongate hollow tubular members, e.g., a catheter,
25 trocars, etc.

[0130] With respect to the anchor assemblies described herein, the types of anchors shown and described are intended to be illustrative and are not limited to the variations shown. For instance, several of the tissue anchor variations are shown as "T"-type anchors while other variations are shown as reconfigurable "basket"-type anchors, which may generally comprise
30 a number of configurable struts or legs extending between at least two collars or support members. Other variations of these or other types of anchors are also contemplated for use in an anchor assembly. Examples of anchors which may be utilized are disclosed in co-pending

U.S. Pat. App. Serial No. 10/612,170, filed July 1, 2003, which is incorporated herein by reference in its entirety. Moreover, a single type of anchor may be used exclusively in an anchor assembly; alternatively, a combination of different anchor types may be used in an anchor assembly. Furthermore, the different types of cinching or locking mechanisms are not
5 intended to be limited to any of the particular variations shown and described but may be utilized in any of the combinations or varying types of anchors as practicable.

[0131] To accomplish the secure placement of anchors having uni-directional anchor movement over the suture in a self-locking manner, various devices and methods may be utilized. Figs. 4A and 4B show side and end views, respectively, of one anchor variation 80
10 which is illustrated in the form of a T-type anchor. Although a T-type anchor is shown, the methods and devices used to cinch the anchor may be utilized in other types of anchors, which will be described below. Variation 80 may generally comprise an anchor body 82 having a circular, rectangular, square, etc., cross-section which defines openings 84 and 86 on opposing sides of the anchor 80. Locking block or member 88 may be slidably disposed
15 within anchor body 82 and define a tapered face 90 on the side of block 88 which tapers to at least one of the openings, in this case opening 86. Openings 84, 86 are preferably aligned with one another although this is not necessary.

[0132] Suture 94 may be routed through opening 84, around locking block 88, and back out through opening 86 such that when anchor body 82 is translated in the direction of arrow 96,
20 anchor body 82 may slide freely over suture 94 due to the manner of tapered face 90 contacting suture 84 within opening 84. However, if anchor body 82 were translated in the opposite direction, tension within suture 94 may pull locking block 88 via suture 94 placed over contact surface 92 such that when block 88 translates in the direction of arrow 98, suture 94 at opening 86 is forced into groove 100 defined along the leading edge of block 88, as
25 shown in Fig. 4B. This cleating action may effectively inhibit or prevent any further movement of anchor body 82 over suture 94. Accordingly, anchor body 82 may be moved uni-directionally relative to suture 94 and a distally located anchor to effectively cinch tissue therebetween.

[0133] Fig. 5 illustrates another cinching anchor in the side view of anchor variation 110.
30 In this variation, anchor body 112 similarly defines openings 114 and 116 through which suture 96 may be routed. Locking block or member 118, which may similarly also define tapered face 120 may be slidably disposed within anchor body 112. Locking block 118 may

be urged via a biasing member, for instance spring 122, to maintain a biasing force against suture 94 passing through anchor body 112. As anchor body 112 is translated over suture 94 in the direction of arrow 96, tapered face 120 may allow suture 94 to pass freely between openings 114, 116. However, if anchor body 112 were to be moved in the opposite direction, biasing member 122 may force locking block 118 to exert a force at its leading edge against suture 94, thereby preventing its movement and allowing only uni-directional movement.

[0134] Yet another locking anchor variation 130 is shown in the side view in Fig. 6. In this variation, anchor body 132 also defines openings 134, 136 through which suture 94 may pass. Within anchor body 132, multiple locking blocks or members 138, 140 may be configured to become biased in opposing directions via biasing members or springs 142, 144, respectively. Each of locking blocks 138, 140 may define an opening through which suture 94 may pass. Thus, when anchor body 132 is slowly moved over suture 94 in a first direction, the anchor may translate freely. However, when moved quickly in the opposite direction, the biasing members 142, 144 may urge their respective locking blocks 138, 140 in directions 146, 148 to create a tortuous path through the blocks and inhibit or prevent the reverse movement of anchor body 132 relative to suture 94.

[0135] Fig. 7 shows a perspective view of another locking anchor variation 150 in which anchor body 152 defines an opening 154 having a tapered or grooved portion 156. Opening 154 may be sized to allow suture 94 to pass through opening 154 such that anchor body 152 may be translated freely relative to suture 94. Once anchor body 152 has been desirably positioned relative to the tissue fold or to the opposing anchor, suture 94 may be manipulated to slide into tapered or grooved portion 156, which preferably defines a diameter which is less than a diameter of suture 94. Sliding suture 94 into tapered or grooved portion 156 may lock a position of anchor body 152 relative to suture 94 due to the cleating effect of grooved portion 156 on suture 94.

[0136] Figs. 8A and 8B show cross-sectional side and top views, respectively, of another locking anchor variation 160 in which anchor body 162 may define a through-hole passage or opening 164 through which suture 94 may pass. Anchor body 162 may have one or several levered, flapped, or biased locking members 166 which may be integrally formed with anchor body 162. These locking members 166 may be formed radially about opening 164 such that when suture 94 is absent, the resting configuration of locking members 166 define an opening 164 having a diameter less than that of the suture 94 passed through. Locking members 166

may be biased to protrude in a single direction, as shown in Fig. 8A, such that when anchor body 162 is moved in a first direction over suture 94, the anchor 162 passes freely. However, when anchor body 162 is moved in the opposing direction over suture 94, locking members 166 engage onto suture 94 and prevent any reverse translation, thereby enabling uni-
5 directional movement and locking of anchor body 162. Although five locking members 166 are shown, any number of members may be utilized as practicable and as desired to effect a desired degree to locking.

[0137] Fig. 8C shows a cross-sectional side view of anchor body 162 in combination with a modified suture 168 having integrated features or protrusions 170 defined along its length.
10 Features or protrusions 170 may be defined uniformly at regular intervals along the length of suture 168 or intermittently, depending upon the desired effects, to enhance the locking ability of the anchor body onto the suture. Moreover, the features or protrusions 170 may be integrally formed protrusions or they may simply comprise knotted sections of suture. Sutures which are modified or knotted may be optionally utilized in any of the locking anchor
15 variations as described herein in place of conventional sutures, depending upon the desired degree of locking and locking effects.

[0138] As shown in the cross-sectional views of Figs. 9A and 9B of locking anchor variations 180 and 188, respectively, anchor body 182 may also comprise biased locking members 184, contained within the anchor body 182. The number and configuration of
20 locking members 184 may be varied as desired and may optionally be apposed, as shown in Fig. 9A, or utilize a single member 184, as shown in anchor variation 188 in Fig. 9B. The figures show knotted suture 186 used with anchor variation 180; however, conventional sutures may also be utilized.

[0139] Fig. 9C shows another modification of suture 94 which may be utilized with any of
25 the anchor locking variations shown herein. The portions of suture 94 which come into contact with the anchor locking mechanisms may be coated with a material having a relatively higher frictional coefficient, i.e., a coefficient of friction that is higher than the underlying suture material. For example, the portion of suture 94 may be coated with a metallic covering or slid within sleeve 181, which may be made of a metallic material such as
30 Titanium, Nitinol, stainless steel, etc. to enhance the locking force between suture 94 and the anchor. As shown in the figure, if sleeve 181 is utilized, the ends 183, 185 of sleeve 181 may

be crimped onto suture 94. One or several openings 187 may also be defined along sleeve 181 to further enhance the locking capability between suture 94 and the locking mechanism.

[0140] Aside from the use of mechanical locking features integrated within or with the anchor bodies, locking mechanisms may also utilize a variety of knotting techniques.

5 Conventional knots, which are typically tied by the practitioner either within the body or outside the body and advanced over the suture length, may be utilized for locking the anchor in place relative to the tissue fold and opposing anchor; however, self-locking knots which enable the uni-directional travel of an anchor body relative to the suture and tissue are desirable.

10 [0141] Fig. 10 shows locking anchor assembly 190 with distal anchor 192, which may be positioned distally of a tissue fold, and proximal anchor 194, which may be positioned proximally of a tissue fold or folds. In this variation, suture 94 may be routed through proximal anchor 194 via openings 196, 198 and extended to distal anchor 192. At distal anchor 192, suture 94 may be routed through opening 200 and over pin 202 positioned within
15 distal anchor 192. Pin 202 may function as a pulley over which suture 94 may travel during anchor locking adjustments. Suture 94 may then be routed back towards proximal anchor 194 through opening 204 and define loop 206 through which the proximal portion of suture 94 passes to thereby create a choke-type loop. The terminal end of suture 94 may then be anchored at fixed end 208 within the body of proximal anchor 194.

20 [0142] In operation, when tension is applied to suture 94 or when proximal anchor 94 is advanced distally, proximal anchor 194 and distal anchor 192 may be freely drawn towards one another to secure any tissue fold or folds (not shown for clarity) disposed therebetween. However, if proximal anchor 194 were pulled or urged in the opposite direction away from the tissue or from distal anchor 192, loop 206 would "choke" suture 94 and prevent any
25 reverse movement of proximal anchor 194.

[0143] Fig. 11A shows a perspective view of locking anchor assembly 210 having distal anchor 212 and proximal anchor 214 with suture 94 extending between the two anchors. Terminal end 230 of suture 94 may be knotted or otherwise retained by proximal anchor 214 and routed through opening 216 and back through opening 218 to create looped portion 228,
30 both openings 216, 218 being defined in proximal anchor 214. Suture 94 may be routed from opening 218 and through distal anchor 212 via openings 222, 224. Suture 94 may then be routed back to proximal anchor 214 through an opening 220 and wrapped 226 about looped

portion 228 to continue on proximally. This knotted configuration facilitates advancement of proximal anchor 214 towards distal anchor 212 but chokes suture 94 when proximal anchor 214 is moved in an opposing direction.

[0144] Figs. 11B and 11C show top and cross-sectional side views of an alternative variation on proximal anchor 214 (and distal anchor 212, if desired). As shown, anchor 214 may optionally define grooves or channels 232 which extend at least partially between openings 216, 218, and 220. These grooves or channels 232, as seen in Fig. 11C, may be sized such that any of the overlying suture 94 are cinched or wedged into grooves 232 to facilitate the cinching action of anchor 214 with respect to suture 94.

[0145] Another locking anchor assembly 240 is shown in the perspective view of Fig. 12A, which shows distal anchor 242 and proximal anchor 244 with suture 94 extending between the two anchors. Suture 94 may be routed through opening 246 defined through proximal anchor 244 and passed through distal anchor 242 via openings 250, 252. Suture 94 may then be routed back towards proximal anchor 244 and passed through opening 248 to create at least two adjacent loops (half hitch knots) 254, 256 with looped section 258. During cinching of proximal anchor 244 against the tissue, the knotted suture may be slid distally with proximal anchor 244. Once proximal anchor 244 has been desirably positioned along suture 94, the terminal end of suture 94 may be pulled, as shown by arrow 260, to alter the knot configuration, commonly called changing the dressing of the knot, such that the knot becomes locked onto suture 94 and prevents any reverse movement of proximal anchor 244.

[0146] Fig. 12B also shows a perspective view of another locking anchor variation similar to that shown in Fig. 12A. In this variation, suture 94 may be wrapped into two intertwined loops 264, 266 and further wrapped again into adjacent intertwined loops 262, 268. Distal advancement of the knotted configuration along with proximal anchor 244 may be accomplished until the terminal end of suture 94 is placed under tension, as shown by arrow 260. Tension may be applied once proximal anchor 244 has been desirably positioned along suture 94 to lock the knot into position and prevent any reverse movement of proximal anchor 244 along suture 94.

[0147] Fig. 12C shows a perspective view of another anchor locking assembly similar to the variations above. The knot may be modified by wrapping suture 94 into a first set of several loops, shown as three loops 270, 272, 274, although in other variations, any number of loops may be utilized depending upon the desired locking effects. Suture 94 may then be

wrapped in a second set of several additional loops in a proximally adjacent position about suture 94, shown as loops 278, 280, 282 joined by looped section 276. Likewise, any number of loops in the second set may be utilized either independent of the number of loops in the first set or to mirror the first set of loops. In either situation, once suture terminal end 284 is
5 tightened, a knotted configuration, as shown in Fig. 12D, is formed which may be freely slid along suture 94 provided the knotted configuration itself is pushed along suture 94, e.g., via a pusher tube, knot pusher, etc. However, once tension is applied along suture 94 by proximal anchor 244 pushing against the knot and by the tension created in the suture extending between anchors 242, 244, the knot locks against suture 94 and prevents reverse movement of
10 proximal anchor 244 along suture 94.

[0148] Fig. 12E shows a perspective view of another locking anchor variation similar to the variation shown in Fig. 12D yet having a single suture traverse between anchors 242, 244. In this variation, suture 94 may have terminal end 286 anchored or retained by distal anchor 242 at opening 252 and have a single suture traverse to proximal anchor 244. A second terminal
15 end 288 may also be anchored or retained by proximal anchor 244 at opening 246. The portions of suture 94 extending between proximal anchor 244 and the knot may have a biasing member, e.g., spring 290, disposed over one or both lengths of suture to maintain proximal anchor 244 and the knot under a constant force to ensure that the knot is maintained under a locking force to prevent the reverse travel of proximal anchor 244.

[0149] Yet another variation of a locking anchor variation having a single suture traversing the anchors is shown in the perspective view of Fig. 12F. A terminal end 252 of suture 94 may be anchored or retained at distal anchor 242 and routed to proximal anchor 214 through opening 218. The length of suture 94 may form loop 292 on a first side of proximal anchor 214 and a second loop 296 on the opposite side of proximal anchor 214 between openings
25 216, 220. Suture 94 may then be wrapped about loop 292 via loop 294 on the first side to form an interlocking suture loop. This variation is also effective in allowing proximal anchor 214 to translate over suture 94 towards the tissue and distal anchor 242 yet prevent reverse movement of proximal anchor 214 due to a choking action by the intertwined suture loops on the proximal side of proximal anchor 214.

[0150] Fig. 12G shows a perspective view of another locking anchor variation similar to that shown in Fig. 12F. Here, suture 94 may be routed through opening 220 in proximal anchor 214 to form loop 292 before being passed through openings 218 and 216 and

intertwining loop 294 through loop 292. Likewise, this variation is also effective in allowing proximal anchor 214 to translate over suture 94 towards the tissue and distal anchor 242 yet prevent reverse movement of proximal anchor 214.

[0151] As mentioned above, the locking and cinching mechanisms described herein may be
5 utilized with a variety of different anchor types. For instance, the cinching mechanisms described above may be used not only with T-type anchors but also with reconfigurable basket-type anchors. Described hereinafter are basket-type anchors configured for implantation or placement against tissue in a similar manner as described previously and examples of how cinching mechanisms may be utilized in securing tissue plications.
10 Moreover, additional cinching mechanisms which are preferably utilizable with basket-type anchors are also described below.

[0152] When cinching or locking basket-type anchors, the baskets may be delivered into or through the tissue in the same or similar manner as described above, particularly as shown in Figs. 3A-3G. For example, Fig. 13A shows anchor delivery system 300 in proximity to
15 tissue fold F. Again, tissue fold F may be disposed within a gastrointestinal lumen, such as the stomach, where tissue wall W may define the outer or serosal layer of the stomach. Delivery push tube or catheter 302 may be disposed within launch tube 18 proximally of basket anchor 306, which is shown in a compressed delivery configuration with a relatively low profile when disposed within needle lumen 58 of needle 54. A single basket anchor 306
20 is shown disposed within needle 54 only for illustrative purposes and is not intended to be limited by the number of basket anchors; rather, any number of basket anchors may be disposed within needle lumen 58 as practicable depending upon the desired procedure and anchoring results.

[0153] Suture 94 may be routed through or externally of push tube lumen 304 and further
25 routed within and/or through proximal collar 310 of anchor 306. The terminal end of suture 94 may be routed within anchor 306 and affixed to distal collar 308 in one variation. Alternatively, suture 94 may be affixed or anchored within anchor 306 or at proximal collar 310 depending upon the desired effect and procedure being performed. Moreover, if multiple anchors are utilized in a tissue plication procedure, suture 94 may be routed through anchor
30 306 such that the anchor 306 may freely slide along or over suture 94.

[0154] The basket anchors may comprise various configurations suitable for implantation within a body lumen. Basket anchors are preferably reconfigurable from a low profile

delivery configuration to a radially expanded deployment configuration in which a number of struts, arms, or mesh elements may radially extend once released from launch tube 18 or needle 54. Materials having shape memory or superelastic characteristics or which are biased to reconfigure when unconstrained are preferably used, e.g., spring stainless steels, Ni-Ti alloys such as Nitinol, etc. The basket anchor 306 is illustrated as having a number of reconfigurable struts or arm members 312 extending between distal collar 306 and proximal collar 310; however, this is intended only to be illustrative and suitable basket anchors are not intended to be limited to baskets only having struts or arms. Examples of suitable anchors are further described in detail in U.S. Pat. App. Serial No. 10/612,170, which has already been incorporated herein above.

[0155] Fig. 13A shows basket anchor 306 delivered through tissue fold F via needle 54 and launch tube 18. As above, the other parts of the plication assembly, such as upper and lower bail members 20, 26, respectively, and tissue acquisition member 28 have been omitted from these figures only for clarity.

[0156] Fig. 13B shows one variation where a single fold F may be secured using basket anchor 306'. As seen, basket anchor 306' has been urged or ejected from needle 54 and is shown in its radially expanded profile for placement against the tissue surface. In such a case, a terminal end of suture 94 may be anchored within the distal collar of anchor 306' and routed through tissue fold F and through, or at least partially through, proximal anchor 318, where suture 94 may be cinched or locked proximally of, within, or at proximal anchor 318 via any number of cinching mechanisms 316 described herein. Proximal anchor 318 is also shown in a radially expanded profile contacting tissue fold F along tissue contact region 314. Locking or cinching of suture 94 proximally of proximal anchor 318 enables the adequate securement of tissue fold F.

[0157] If additional tissue folds are plicated for securement, distal basket anchor 306 may be disposed distally of at least one additional tissue fold F', as shown in Fig. 13B, while proximal anchor 318 may be disposed proximally of tissue fold F. As above, suture 94 may be similarly affixed within distal anchor 306 and routed through proximal anchor 318, where suture 94 may be cinched or locked via proximal anchor 318, as necessary. If tissue folds F and F' are to be positioned into apposition with one another, distal basket anchor 306 and proximal anchor 318 may be approximated towards one another. As described above, proximal anchor 318 is preferably configured to allow suture 94 to pass freely therethrough

during the anchor approximation. However, proximal anchor 318 is also preferably configured to prevent or inhibit the reverse translation of suture 94 through proximal anchor 318 by enabling uni-directional travel of anchor 318 over suture 94. This cinching feature thereby allows for the automated locking of anchors 306, 318 relative to one another during anchor approximation.

[0158] Aside from the anchor cinching or locking mechanisms utilizing looped and knotted sutures for facilitating uni-directional locking, various mechanisms utilizing friction may also be implemented. Figs. 14A and 14B show cross-sectional side views of one variation in cinching assembly 320. Proximal collar 322, proximal portions of struts 312, and distal portions of launch tube 18 are shown and other features of the assembly and tissue fold F have been omitted from the figure only for clarity.

[0159] A locking or cinching collar or collet 326 may be positioned within launch tube 18 proximally of anchor collar 322. Cinching collet 326 may comprise a cylindrically shaped member defining a lumen therethrough for passage of suture 94. A distal end of cinching collet 326 may have at least one and preferably several clamping arms or teeth 328 which are configured to cinch or clamp down upon suture 94 passing through. Proximal anchor collar 322 may be sized to correspondingly receive cinching collet 326 therewithin to create an interference fit relative to an outer diameter of cinching collet 326. A distal portion of anchor collar 322 may also define a tapered or angled portion 324 such that when cinching collet 326 is advanced within anchor collar 322, angled portion 324 may effectively force clamping arms or teeth 328 to cinch radially inward upon suture 94.

[0160] In operation, once proximal anchor 318 has been desirably positioned relative to tissue fold F and/or the distal anchor and with proximal collar 322 positioned within launch tube 18, delivery push tube 302 may be advanced distally to urge cinching collet 326 into anchor collar 322 such that clamping arms or teeth 328 are clamped onto suture 94 and cinching collet 326 is friction-fitted within anchor collar 322. Anchor collar 322 may then be urged out of launch tube 18 and the anchor left against the tissue surface.

[0161] Another cinching assembly variation 330 is shown in the cross-section view of Figs. 15A and 15C. Launch tube 18 has been omitted from these figures for clarity only. Delivery push tube 332 is shown as defining suture lumen 334 and locking member or pin lumen 336 therethrough. Although two separate lumens are shown, a single common lumen may be utilized in alternative variations. With proximal anchor collar 344 positioned distally of push

tube 332, suture 94 may be routed through suture lumen 334 and through collar lumen 346. Locking member or pin 338 may be positioned within lumen 336 proximally of collar lumen 326. Fig. 15B shows an end view of push tube 332 with locking pin 338 and suture 94 positioned within prior to cinching of the anchor.

5 [0162] Once the anchor has been desirably positioned relative to the tissue, suture 94 may be pulled proximally such that anchor collar 344 rests against the distal end of push tube 332. Locking pin 338, which may define a tapered or radiused end 340 to facilitate its insertion into collar lumen 346, may be urged distally via push rod 342 to force locking pin 338 into anchor collar 344 such that the portion of suture 94 within anchor collar 344 becomes
10 effectively wedged and thereby prevents further movement of the anchor along suture 94. Fig. 15C shows a cross-sectional side view of locking pin 338 having been urged into anchor collar 344 in a frictional engagement with suture 94. Fig. 15D shows a cross-sectional end view of collar 344 with locking pin 338 and suture 94 positioned within.

[0163] Fig. 15E shows a perspective view of another cinching variation 331 which is
15 similar to the variation described above. One or more tapered pins or blocks 339 may be slidably disposed within tapered channel 335 defined in proximal collar 333. The figure shows two tapered pins 339, although a single pin may be utilized or more than two pins may also be used. If two or more pins 339 are utilized, suture 94 may be passed between the pins 339. Pins 339 may be free to slide along inner surface 337 of channel 335 in the direction of
20 arrows 345 depending upon the direction of travel of suture 94 through channel 335. Fig. 15F shows a perspective view of only pins 339 for clarity; as seen, pins 339 may be tapered distally from a larger diameter to a smaller diameter and although pins 339 are shown as semi-circularly shaped members, contact surface 341 may be curved or arcuate to better contact suture 94. Moreover, contact surface 341, which contacts suture 94 passing through
25 channel 335, may define a roughened surface or it may alternatively define a plurality of serrations, teeth, projections, etc., to facilitate contact against suture 94.

[0164] In use, as proximal collar 333 is translated in the direction of arrow 343, pins 339 may be forced proximally such that suture 94 may pass freely through channel 335. However, if proximal collar 333 were to be translated in the opposing direction, pins 339 may
30 be forced in the opposite direction to cinch down upon suture 94 within channel 335 and thereby inhibit any further motion.

[0165] An alternative variation of the assembly is shown in the cross-sectional views of Figs. 15G and 15H, which show a cinching anchor having a retractable pin. Fig. 15G shows proximal collar 347 with one or more retracting arms 349 extending proximally from collar 347. Retracting arms 349 may be configured to pivot at bend 353 when urged via a
5 compression force applied at bend 353 in the direction of arrows 355. The application of this compression force may urge pin support collar 357 which is defined at a proximal portion of arms 349, to move in the direction of arrow 359. This in turn may move pin 351, which extends from pin support collar 357, proximally out of proximal collar 347 to thereby release suture 94 from its locked position. In one variation, retracting arms 349 may be biased to
10 retain pin 351 within proximal collar 347 unless a compression force is applied at bend 353.

[0166] Figs. 16A and 16B show cross-sectional side views of another variation of cinching assembly 350. Cinching assembly 350 may generally comprise outer tubing 352 and inner tubing 358 rotatably positioned within outer tubing lumen 354. Cinching member 362 may be positioned distally of outer tubing 352 and may generally comprise a collar base 364 and
15 cinching collar 374 projecting proximally from collar base 364. Cinching collar 374 is preferably tapered and threaded and may also be longitudinally slotted such that rotatable collar 368 may be rotatably disposed upon slotted cinching collar 374. A distal end of outer tubing 352 may define one or several engaging members 356 which are adapted to engagingly contact detents or keyed engagement interfaces 366 located on collar base 364.
20 Inner tubing 358 may also define one or several engaging members 363 which are also adapted to engagingly contact detents or keyed engagement interfaces 372 located on the rotatable cinching collar 374. Suture 94 may be routed through inner tubing lumen 360, through cinching collar 374, and through proximal anchor collar 310.

[0167] In operation, suture 94 may pass freely through assembly 350. Once the anchor has
25 been desirably positioned, engaging members 356 on outer tubing 352 may be correspondingly engaged against interface 366 and engaging members 363 on inner tubing 358 may be engaged against interface 372. With suture 94 tensioned appropriately, outer tubing 352 may be held stationary while inner tubing 358 is rotated to torque rotatable collar 368 about threaded cinching collar 374. As rotatable collar 368 is torqued onto cinching
30 collar 374, the tapered shape may urge the slotted members to cinch upon suture 94 passing therethrough. Stand-offs 370, which may protrude from rotatable collar 368, may be adjusted in height to control how far rotatable collar 368 may be torqued onto collar base 364 such that the degree to which rotatable collar 368 is torqued about cinching collar 374 may be

desirably adjusted. Once the cinching collar 374 has been desirably cinched onto suture 94, proximal anchor collar 310 may be ejected from launch tube 18 along with the cinching assembly, as shown in Fig. 16B.

[0168] Another variation on cinching assembly 380 may be seen in the cross-sectional views of Figs. 17A and 17B. Assembly 380 is similar to cinching assembly 330 shown above in Figs. 15A to 15D. Delivery push tube 332 and push rod 342 have been omitted from these figures only for clarity. In this variation, when locking pin 338 is pushed distally into proximal collar 388, a retaining tube member 384 may be utilized to provide a counterforce to stabilize proximal collar 388 during cinching. Retaining tube member 384 may generally comprise one or several collar engaging arms 386 for engaging proximal anchor collar 388 at collar detents 390 defined along anchor collar 388. During the insertion of locking pin 338 into collar 388, collar engaging arms 386 may be positioned within launch tube 18 or within retractable sleeve 382. After locking pin 338 has been inserted within anchor collar 388, engaging arms 386 may be advanced distally out of launch tube 18 or retractable sleeve 382 may be withdrawn proximally to expose engaging arms 386. Once free of any constraining forces, engaging arms 386 may be biased to spring or open radially to then release proximal anchor collar 388 in a cinched configuration.

[0169] Another variation on cinching assembly 400 is shown in Figs. 18A to 18D, in which proximal anchor collar 406 may comprise one or several biasing members or cinching tabs 408 within collar 406. Each of the tabs 406 may be biased to project inwardly such that suture 94 passing through is automatically cinched and locked in position, as shown in Fig. 18A. A suture release member 404, which may generally comprise a cylindrically shaped tube or member having a tapered surface 410 and a suture lumen 412 defined therethrough, may be positioned within anchor collar 406 during anchor positioning to allow free passage of suture 94 through the anchor, as shown in Fig. 18B. Fig. 18C shows an end view of release member 404 defining suture lumen 412 extending therethrough. Fig. 18D shows a perspective view of release member 404 to show tapered surface 410 and suture lumen 412 in better detail. Tapered surface 410 may be omitted but is preferably to facilitate the insertion and removal of release member 404 from anchor collar 406. When the anchor has been desirably positioned and is ready to be locked in place over suture 94, tubular member 402 may engage suture release member 404 for withdrawal from anchor collar 406. The removal of release member 404 may cause cinching tabs 408 to lock upon suture 94 and prevent the further movement of the anchor relative to suture 94.

[0170] Figs. 19A and 19B show another variation of cinching assembly 420 in which a deformable cinching member 424 may be positioned within the anchor distally of anchor collar 422. Cinching member 424 may define a tapered outer surface such that when the anchor is ready to be secured to suture 94, the insertion of cinching member 424 into collar 422 may compress cinching member 424 about suture 94 such that any further movement of the anchor is prevented. Cinching member 424 may be pulled into anchor collar 422 via pull wire 426, which may be manipulated at its proximal end by the surgeon or user when desired.

[0171] Figs. 20A to 20D show cross-sectional views of another variation in cinching assembly 430. As shown in Fig. 20A, proximal anchor collar 432 may comprise a pivotable locking member 434 contained either within anchor collar 432 or proximally of collar 432. This example illustrates locking member 434 contained within collar 432. Suture 94 may pass through locking member 434, which is shown in the end view of collar 432 in Fig. 20B, as having two pivots 436. Moreover, locking member 434 and pivots 436 may be integrally formed from proximal collar 432. Pivoting locking member 434 may be biased to rotate about pivot 436 such that a resting position of locking member 434 is against an inner surface of collar 432. During distal anchor translation over suture 94, tension as represented by arrow 438, on suture 94 may force pivot 434 into an open position where suture 94 may pass freely through. Upon having desirably positioned the anchor against tissue, locking member 436 may be biased to pivot in direction 440 to lock suture 94 against the inner surface of collar 432. Opposite movement of the anchor relative to suture 94 may act to further cinch locking member 434 against suture 94 and thereby further inhibit the movement of the anchor in the reverse direction.

[0172] A similar variation is shown in the cross-sectional side and perspective views of Figs. 20E and 20F, respectively. In this variation, locking member 434' may extend proximally of proximal collar 432 at an angle relative to collar 432. Locking member 434' may be pivotable via pivot 436' such that locking member 434' may pivot in the direction of the arrows shown depending upon the direction which the tissue anchor is translated relative to suture 94. If proximal collar 432 is translated distally over suture 94, it may travel freely; however, if proximal collar 432 is translated proximally in the opposite direction, suture 94 may become wedged in a tapered portion of opening 442 through which suture 94 passes. Once suture 94 is wedged in tapered opening 442, locking member 434' may pivot towards proximal collar 432, where it is stopped from further motion, thereby locking the tissue anchor onto suture 94 and preventing its reverse motion.

[0173] Figs. 21A and 21B show another cinching assembly variation 450 as seen in the cross-sectional side views. In this variation, delivery push tube 452 may be disposed proximally of locking collar 454 and proximal tapered anchor collar 458. Once the anchor has been desirably positioned relative to the tissue fold F, with suture 94 under tension, locking collar 454 may be urged distally via push tube 452 such that locking collar 454 slides over proximal anchor collar 458. An inner surface of locking collar 454 may be tapered and anchor collar 458 may also be tapered in a correspondingly opposed manner such that when locking collar 454 is mated with anchor collar 458, anchor collar 458 may cinch locking collar 454 upon suture 94 to thereby prevent any further movement of the anchor over suture 94. Both collars may be made from any of the same or similar materials, as described above.

[0174] In addition to friction-based locking and cinching mechanisms utilizable in tissue anchors, other mechanisms which create tortuous paths for the suture within or through the anchors may also be utilized for creating uni-directional locking.

[0175] One cinching anchor variation 460 is shown in the cross-sectional side view in Fig. 22A. As shown, suture 94 may be routed through anchor proximal collar 462 and looped over pulley or pin 466 contained within distal collar 464. Suture 94 may then be routed back through and looped 468 about suture 94 and tied with slip knot 470. As tension is applied to suture 94, slip knot 470 may prevent further movement of the anchor relative to suture 94.

[0176] Figs. 22B and 22C show a variation which may be used in combination with cinching anchor variation 460 or alone. Pin 474 may optionally be positioned within proximal collar 462 and suture 94 may be wrapped or looped about itself around pin 474 in a manner as shown in the detail view of Fig. 22C. The configuration of loop 472 may allow for the uninhibited translation of the anchor in the direction of the arrow as shown; however, when the anchor is moved in the opposite direction, loop 472 may effectively cinch upon itself to thus prevent or inhibit the reverse motion of the anchor relative to suture 94.

[0177] Another cinching variation is shown Figs. 22D and 22E. Suture 94 may be routed through proximal collar 462 with an additional length of cinching suture 476. The distal end of cinching suture 476 may form loop 478 which is wrapped about suture 94 and free to slide over suture 94. After the anchor has been desirably positioned relative to the tissue and with suture 94 preferably under tension, cinching suture 476 may be pulled proximally such that loop 478 is pulled into proximal collar 462 and becomes wedged against suture 94. The multiple lengths of suturing material utilized for loop 478 and suture 94 preferably form a

cross-sectional area which is larger than an inner diameter of proximal collar 462 such that positioning loop 478 and suture 94 within collar 462 ensures a frictional lock which prevents further movement of the suture 94 relative to the anchor. Suture 94 and cinching suture 476 are preferably made from the same or similar materials although differing suture materials
5 may also be used.

[0178] Fig. 23 shows a cross-sectional view of cinching assembly variation 480 in which proximal collar 482 may comprise pulley or pin 484 about which suture 94 may be looped once or several times 490. Distal collar 486 may also comprise pulley or pin 488 about which suture 94 may also be looped once or several times before being wrapped or looped
10 492 back about suture 94. The terminal end of loop 492 may be secured about suture 94 via slip knot 494. This configuration of looping allows for the anchor to be advanced uni-directionally relative to the suture and tissue, yet prevents or inhibits the reverse movement of the anchor and thus effectively enables the tissue to be cinched via the anchors.

[0179] Another cinching or locking anchor variation 500 is shown in the cross-sectional view of Fig. 24A. In creating a tortuous path for suture 94, cinching sleeve 506 may be positioned proximally of proximal collar 504 within or distally of delivery push tube 502. Cinching sleeve 506 may generally comprise a tubular structure having sleeve lumen 510 defined therethrough and a number of openings 508 defined along the length of sleeve 506. Openings 508 may be uniformly patterned along sleeve 506 or they may be randomly
20 positioned. Moreover, any number of openings 508 may be utilized as practicable. In either case, suture 94 may be routed in various patterns throughout openings 508 and through sleeve lumen 510 before being routed through proximal collar 504. Once the anchor is to be locked, cinching sleeve 506 may be urged distally via delivery push tube 502. When urged or pushed distally, this may be done slowly so as to allow suture 94 to pass through the tortuous path
25 created by suture 94 passing through openings 508. However, once cinching sleeve 506 has been advanced proximally adjacent to proximal collar 504, cinching sleeve 506 may become locked with proximal collar 504 pressing against sleeve 506.

[0180] Fig. 24B shows another variation of a cinching mechanism which utilizes a tortuous path. Cinching sleeve 512 may comprise a tubular structure having an opening 514 defined
30 along a surface of sleeve 512 through which suture 94 may pass. Cinching sleeve 512 may be disposed within proximal collar 504 with suture 94 routed from outside of sleeve 512 and passing to within sleeve 512 through opening 514. In operation, because of the manner in

which suture 94 is routed through sleeve 512 and into the anchor, distal translation of the anchor relative to the tissue and suture 94 is uninhibited. But when the anchor is reversed in direction relative to suture 94, suture 94 and cinching sleeve 512 may be drawn into the anchor and become locked due to the interference between suture 94, cinching sleeve 512, and proximal collar 504. Accordingly, an outer diameter of cinching sleeve 512 is preferably sized to be slightly less than an inner diameter of proximal collar 504 such that when suture 94 is passed through opening 514, cinching sleeve 512 becomes wedged against collar 504. Cinching sleeve 512 may be made from any of the same or similar materials as the anchors, as described above.

[0181] Figs. 24C and 24D show another variation similar to cinching sleeve 512 described above. Cinching sleeve variation 516 may be similarly sized as sleeve 512 and may also similarly define an opening 514; however, sleeve 516 includes one or several retaining arms 518 defined on a distal end of sleeve 516. Any number of retaining arms 518 may be utilized provided that they extend radially and reside distally of proximal collar 504 such that they prevent sleeve 516 from sliding proximally out of collar 504. Fig. 24D shows a perspective view of cinching sleeve 516 with retaining arms 518 radially extended from the body of sleeve 516. Cinching sleeve 516 may also be made from the same or similar material as the anchor; for example, sleeve 516 may be fabricated from a material having superelastic characteristics, such as Nitinol. Accordingly, when cinching sleeve 516 is initially inserted through collar 504 and/or during anchor delivery through launch tube 18 into or through the tissue, retaining arm or arms 518 may be configured into a low profile with arm or arms 518 constrained into a tubular shape. Upon anchor release or upon being inserted through collar 504, retaining arms 518 may be released to extend radially.

[0182] Yet another variation 520 on cinching assembly is shown in Fig. 25A. Generally, assembly variation 520 may comprise cinching collar 522 located proximally of anchor proximal collar 524. Cinching collar 522 may be a tubular structure having superelastic material characteristics, such as those found in Nitinol. Obstructing members 526, which may be formed from portions of cinching collar 522, may be pressed or formed to extend into a lumen of cinching collar 522 such that a tortuous path is created for the passage of suture 94. Although three obstructing members 526 are shown in the figure, any number of obstructions as practicable may be created depending upon the desired tortuous path to be created.

[0183] Assembly 520 shows cinching collar 522 as a separate collar located proximally of anchor collar 524; however, the cinching collar may be integrated with the anchor collar such that a singular integral structure is formed, as shown in anchor variation 530 in the cross-sectional view of Fig. 25B. In either alternative during anchor placement relative to the tissue fold, retaining sleeve 534 may be inserted within cinching collar 522 to maintain obstructing members 526 in an open position for allowing suture 94 to pass freely through sleeve 534. Once the anchor has been desirably positioned, retaining sleeve 534 may be withdrawn, as shown in the perspective view of Fig. 25C, using any number of methods. Removal of retaining sleeve 534 will allow for obstructing members 526 to reconfigure inwardly in the direction of arrows 532 to thus reconfigure cinching collar 522 into a tortuous path.

[0184] Cinching assembly 540 may also utilize a single or any number of tabs or levers to aid in capturing suture 94 and/or creating a tortuous path for suture 94 to traverse. As shown in the cross-sectional view of Fig. 26A, proximal collar 542 may have a pivoting lever 544 formed integrally from a side wall of proximal collar 542. Alternatively, lever 544 may be included in a cinching collar separate from proximal collar 542. Lever 544 may be biased to spring inwardly into proximal collar 542 upon suture 94 passing therethrough. During translation of the anchor in a first direction, suture 94 may be allowed to freely pass through proximal collar 542 and past lever 544 due to its pivoting motion. When the anchor is moved or urged in the reverse direction, lever 544 may act to cinch down upon suture 94 against an inner surface of proximal collar 542, as shown in the figure.

[0185] Another variation 546 of assembly 540 is shown in the cross-sectional view of Fig. 26B in which proximal collar 548 is shown as having at least two levers 550, 552 both biased in opposing directions to create a tortuous path for suture 94 to traverse. In either variation, the cinching levers may be configured to prevent or inhibit the over-cinching or cutting of suture 94. Figs. 26C and 26D show alternative end views of Fig. 26A. Uni-directional lever 544, as seen in Fig. 26C, may be formed from the side wall of proximal collar 542 such that when lever 544 cinches down upon suture 94, the corners or ends of lever 544 contact an inner surface of proximal collar 542 at contact points 554. The contact which occurs may ensure that an open space 556 is preserved and that lever 544 is prevented from over cinching onto suture 94 within space 556 and cutting suture 94. Fig. 26D shows an alternative uni-directional lever 544' which defines a curved or arcuate edge 558 which contacts suture 94. The arcuate edge 558 may prevent the over cinching onto suture 94 and cutting of suture 94.

[0186] Figs. 26E, 26F, and 26G show alternative variations of cinching assembly 546 with uni-directional levers having various configurations. Fig. 26E shows a cross-sectional side view of cinching assembly 560 in which proximal collar 562 may have levers 564, 566 directed and biased in opposing directions to create a tortuous path. Each of the levers 564, 566 in this variation may be curved inwardly towards proximal collar 562. Fig. 26F shows a cross-sectional side view of cinching assembly 568 in which proximal collar 570 has uni-directional levers 572, 574 angled towards one another when biased inwardly. And Fig. 26G shows a cross-sectional side view of cinching assembly 576 in which proximal collar 578 has uni-directional levers 580, 582 curved outwardly relative to one another when the levers are biased within collar 578.

[0187] Figs. 27A and 27B shows yet another variation of cinching assembly 590 which utilizes a reconfigurable hollow member for cinching suture 94. As shown in Fig. 27A, hollow member 594 may be constrained within tubular delivery member 592 to retain an elongate shape with suture 94 passing uninhibited therethrough. When the anchor is to be cinched, hollow member 594 may be advanced distally from tubular member 592 and when hollow member 594 has been ejected, it may adapt to reconfigure itself into a crimped configuration 594' having a non-linear passageway. Suture 94 passing through the crimped configuration 594' may be inhibited from passing freely therethrough by crimp 596 created within the hollow member. Hollow member 594 may have a variety of cross-sectional shapes, e.g., circular, rectangular, square, hexagonal, etc., and it is preferably made from a material having shape memory characteristics, e.g., Nitinol, such that when hollow member 594 is unconstrained, it may automatically reconfigure into its crimped configuration 594'.

[0188] Another variation of cinching assembly 600 which is configured to reconfigure itself upon being unconstrained is shown in the cross-sectional views of Figs. 28A to 28C. In this variation shown in Fig. 28A, cinching collar 602 may comprise at least two circular members, first collar 606 and second collar 608, connected by an elongate bridging member 604. Cinching collar 602 may be positioned within launch tube 18 proximally adjacent to proximal collar 610 and adapted to reconfigure itself once released from launch tube 18 such that a tortuous path is created for suture 94. Fig. 28B shows an alternative variation in the cinching collar which may be an integrated variation with the proximal collar such that first collar 606 is connected directly to the anchor via joining member 612. In either variation, once the cinching collar has been ejected from launch tube 18, the collar may configure itself such that first collar 606 and second collar 608 are biased towards one another to form, e.g., a

“C”-shape as shown in Fig. 28C. The tortuous path which is created by cinching collar 602 for suture 94 to follow may be sufficient to prevent the further translation of the anchor relative to suture 94. Figs. 28D and 28E, respectively, show perspective views of cinching collar 602 in a constrained delivery configuration and an unconstrained cinching configuration.

[0189] Fig. 28F shows a cross-sectional side view of another cinching assembly which is similar to the variation shown in Fig. 28B. Rather than having first collar 606 and joining member 612 reconfigure itself into a semi-circular shape relative to the anchor, first collar 606 may reconfigure itself to maintain its orientation relative to the anchor while joining member 612 may be formed to curve appropriately or approximately in an “S”-type configuration. The reconfigured cinching member may act to lock suture 94 relative to the anchor when the anchor is moved in a reverse direction.

[0190] Another configuration for a cinching assembly is shown in the side view of Fig. 28G, which shows cinching member 616 located proximally of proximal collar 614.

15 Cinching member 616 may be fabricated from a variety of materials, e.g., Nitinol, spring stainless steel, etc., which exhibit shape memory or superelastic characteristics, or aspects thereof. In use, cinching member 616 may be configured into an elongate delivery configuration. When the tissue anchor is to be cinched or locked relative to the tissue, cinching member 616 may be released from a constraining force such that cinching member

20 616 reconfigures itself into an expanded or extended configuration which creates a tortuous path for suture 94 which sufficiently locks suture 94 within cinching member 616.

[0191] Cinching member 616 may be comprised generally of an elongate bar, ribbon, cylinder, etc., or any elongate member having a diameter or cross-sectional area in its delivery configuration which is sufficiently small to be disposed and/or translated within

25 launch tube 18. Cinching member 616 may define a plurality of openings 618 along the length of cinching member 616 such that when cinching member 616 is in its elongate delivery configuration, as shown in Fig. 28G, suture 94 may be interwoven through openings 618 along a relatively straightened path. Openings 618 may be located along cinching member 616 at uniform locations or they may be randomly positioned along the length of

30 cinching member 616. When released, cinching member 616 may reconfigure itself into an expanded suture-locking configuration 616' which is sufficiently large to prohibit its passage into or through proximal collar 614, as shown in Fig. 28H. Expanded configuration 616' may

comprise any reconfigured shape so long as the expanded shape is adapted to create the tortuous path for suture 94 and is large enough so that passage through proximal collar 614 is not possible.

5 [0192] Other cinching and locking mechanisms which utilize mechanical clamping or crimping to achieve locking of the suture within or through the anchors may also be used to facilitate uni-directional locking.

[0193] For instance, cinching assembly 620 may be seen in the cross-sectional view of Figs. 29A and 29B. Fig. 29A shows delivery tube member 622 having crimping collar 624 disposed therewithin proximally of anchor proximal collar 626. Suture 94 may be passed
10 through both crimping collar 624 and proximal collar 626. Once the anchor has been desirably positioned, crimping collar 624 may be advanced distally adjacent to proximal collar 624 and mechanically crimped 624' down upon suture 94 to create a lock and prevent the reverse movement of the anchor over suture 94, as shown in Fig. 29B. The crimping may be accomplished via mechanical graspers or pinchers configured to clamp down upon collar
15 624. Similarly, Fig. 30A shows cinching assembly 630 in which the crimping collar 632 may be integral with the anchor rather than being a separate member. Fig. 30B shows a mechanically crimped collar 632' which eliminates the need for a separate collar.

[0194] To accomplish mechanical crimping upon a cinching collar, various methods may be utilized. Fig. 31A shows one variation of a tool assembly 640 which may be adapted to
20 apply a mechanical crimping force upon a crimping collar. As seen, launch tube 18 may have delivery push tube 642 located therewithin and positioned proximally of proximal collar 652 of the tissue anchor. Push tube 642 may be used to hold and/or eject proximal collar 652 from launch tube 18. Crimping device 644 may be advanced within launch tube 18 via crimping control member 646, which may be manipulated from its proximal end.

25 [0195] A collar retaining channel 650 may be defined in a distal end of crimping device 644 and adapted to receive and securely hold proximal collar 652 within during a clamping or crimping process. Crimping members or arms 648 may be positioned within crimping device 644 on either side of retaining channel 650. When proximal collar 652 or crimping sleeve is to be clamped or crimped, crimping members or arms 648 may be driven into contact with
30 proximal collar 652 to crimp the collar. Moreover, crimping arms 648 may be actuated through a variety of methods, e.g., hydraulically, pneumatically, via mechanical leverage, etc.

[0196] An alternative crimping assembly 660 is shown in the cross-sectional view of Fig. 32A. Crimping device 662 may be seen within launch tube 18 extending from crimping control member 664. Collar retaining channel 672 may be likewise defined within crimping device 662 for retaining proximal collar 670 during a crimping procedure. This variation may utilize a separate elongate crimping member 666 having actuatable crimping arms 668 positioned at a distal end of elongate member 666. In use, with proximal anchor collar 670 positioned within retaining channel 672, elongate member 666 may be advanced distally until crimping arms 668 are positioned over proximal collar 670 and crimped down. Fig. 32B shows an exploded perspective view of the crimping assembly.

10 [0197] Figs. 31B to 31D show side, end, and perspective views, respectively, of one variation of an anchor proximal collar 652 which is adapted for crimping upon a suture passing therethrough. To facilitate crimping of the collar 652, a circumferential slot 656 may be defined through collar 652 partially around its circumference. Another longitudinal slot 658 may be defined through collar 652 extending longitudinally from a proximal edge of collar 652 to circumferential slot 656. These slots 656, 658 may define at least two crimping arms 654 which may be crimped down upon a length of suture passing through collar 652.

[0198] Aside from the crimping mechanisms described above, additional measures may be optionally implemented to facilitate the cinching or locking of an anchor. Other measures may also be taken to inhibit any damage from occurring to the suture routed through an anchor.

20 [0199] To ensure that the integrity of suture 94 is maintained in the presence of metallic basket anchors 682 and to ensure that suture 94 is not subjected to any nicks or cuts, the portion of suture 94 passing through basket anchor 682 may be encased in a protective sleeve 690, as shown in the perspective view of Fig. 33A of anchor-sleeve assembly 680. The basket anchor 682 is shown in this variation as having anchor struts or arms 688 in a partially deployed configuration. Sleeve 690 may extend between distal collar 684 and proximal collar 686 to prevent excessive contact between suture 94 and elements of basket anchor 682. Fig. 33B shows an end view of the anchor-sleeve assembly 680 showing the relative positioning of sleeve 690 relative to suture 94 and anchor collar 686. Sleeve 690 may be made from a variety of polymeric materials, e.g., polypropylene, PTFE, etc., provided that the material is suitably soft.

[0200] Fig. 34A shows a cross-sectional view of cinching assembly 700 which may be implemented with any of the cinching and locking mechanisms described above. This particular variation utilizes the partial cold-flowing of the engaged suture 94 to enhance the locking or cinching effect of the tissue anchor. The cinching collar, or in this variation proximal collar 702, against which suture 94 is wedged may have multiple through-holes 704 defined over the surface of collar 702. The cross-sectional side view shows suture 94 wedged within collar 702 against locking pin 338. The portion of suture 94 which is adjacent to through-holes 704 may have regions which cold-flow partially into through-holes 704, as shown by cold-flowed suture material 706. These portions of suture material 706 may enhance the locking aspects of suture 94 against collar 702. Fig. 34B shows a perspective view of collar 702 with multiple through-holes 704 defined over the body of collar 702. Through-holes 704 may be defined in a uniform pattern; alternatively, they may be randomly defined over collar 702 or only over portions of collar 702.

[0201] Figs. 35A to 35E show an alternative variation 710 for locking a tissue anchor relative to suture 94. An outer sleeve 720 which is preferably comprised of a polymeric material capable of at least partially flowing when heated, e.g., PTFE, may be disposed circumferentially about an electrically conductive inner sleeve 722. As shown in the perspective views of Figs. 35B and 35C, inner sleeve 722 may be disposed within lumen 726 of outer sleeve 720. Inner sleeve 722 may randomly or uniformly define a plurality of openings or through-holes 724 over the surface of inner sleeve 722.

[0202] In operation, outer and inner sleeves 720, 722, respectively, may be positioned within delivery push tube 716 proximally of proximal collar 718 with suture 94 passing therethrough. When the tissue anchor has been desirably positioned and suture 94 has also been desirably tensioned, an induction unit 712 having one or more induction coils 714 therewithin may be positioned circumferentially (or at least partially circumferentially) about outer and inner sleeves 720, 722. Induction unit 712 may be configured to be disposed within the launch tube 18 or it may be configured to be advanced over or positioned upon launch tube 18. Thermal energy or electrical energy in various forms, e.g., RF, microwave, etc., may be delivered to induction coils 714 such that the energy heats inner sleeve 722, which may be positioned within induction coils 714, as shown in Fig. 35A. As inner sleeve 722 is heated via induction, the inner surface of outer sleeve 720 may be partially melted or deformed such that the material flows at least partially through or within through-hole 724 and contacts suture 94 positioned within inner sleeve 722. The flowed material may cool and act to lock

outer and inner sleeves 720, 722 onto suture 94. Induction unit 712 may then be removed from the area leaving outer and inner sleeves 720, 722 locked relative to the tissue anchor.

[0203] Although inner sleeve 722 shows through-holes 724 as circularly defined openings, other shapes may be utilized. For example, Fig. 35D shows a perspective view of one inner sleeve variation 728 having longitudinally defined slots 730. Alternatively, Fig. 35E shows a perspective view of another inner sleeve variation 732 having circumferentially defined slots 734. Any variety of opening shapes may be utilized so long as the opening or openings allow for material from the outer sleeve 720 to flow through into contact with the suture positioned within.

10 [0204] Other configurations for the anchor itself may also be utilized in conjunction with any of the cinching apparatus described herein. For instance, the linear cinching member 616 shown in Figs. 28G and 28H may also be utilized to function as an anchor itself. Such a linear anchor may be fabricated from a metal, e.g., Nitinol, spring stainless steel, etc., which exhibit shape memory or superelastic characteristics, as described above.

15 [0205] Alternatively, an elongate linear anchor may be comprised of a flexible polymeric material such that the anchor remains in a linear configuration when disposed within a delivery tube for deployment. Examples of potential polymeric materials may include, e.g., polyethylene, polyester, polystyrene, polycarbonate, nylon, teflon, elastomers, etc. However, once the elongate anchor is ejected or deployed from the delivery tube, the anchor may be
20 configured to compress longitudinally, i.e., along the length of the anchor, upon the application of a force in a longitudinal direction relative to the anchor such that portions of the linear anchor bow or expand in a radial direction. The anchors may be configured to bow or expand through a number of techniques such as heat-setting the material. Additional methods and variations are described below in further detail.

25 [0206] Fig. 36A shows a perspective view of one variation 740 of a linear anchor. In this variation, the linear anchor 740 may generally comprise an elongate ribbon or flattened wire 742 having at least one or more openings 744 defined through the anchor 740 along its length. Linear anchor 740 may generally range anywhere in length from, e.g., 3.50 to 7.25 inches, or greater. The thickness of linear anchor 740 may also range from, e.g., 0.010 to
30 0.020 inches, and is preferably 0.013 inches, while the width may range from, e.g., 0.030 to 0.065 inches, and is preferably 0.050 inches.

[0207] Ribbon 742 illustrates openings 744 in an optionally offset pattern relative to one another along the length to enhance the ribbon 740 twisting or bowing effect when compressed linearly. Alternatively, openings 744 may be linearly aligned along the length, if desired. Moreover, this variation illustrates openings 744 uniformly spaced apart from one another anywhere from, e.g., 0.375 to 0.750 inches, over the length of anchor 740.

5 Alternatively, openings 744 may vary in diameter, e.g., 0.015 inches, so long as the length of suture being routed or interwoven through openings 744 is able to freely slide through openings 744.

[0208] One or both ends 748 of ribbon 742 may be optionally configured to be atraumatic by having a blunted end or a tapered end to reduce or inhibit damage to the surrounding tissue. The regions 746 of ribbon 742 located between openings 744 may be configured to flex in a predetermined orientation when anchor 740 is linearly compressed such that the compressed and expanded ribbon 742 expands in a predetermined orientation, as described further below.

10

[0209] Fig. 36B shows a perspective view of another variation 750 of ribbon 752 which is similar to variation 740 of Fig. 36A. Variation 750 defines a plurality of openings 754 which may be defined in a varied offset pattern, e.g., pairs of openings 754 may be offset relative to one another, as shown.

15

[0210] In order to ensure the collapse of the ribbon into a bowed or expanded pattern, the suture may be routed through each, or at least several, of the openings. Fig. 37A shows the ribbon 742 of Fig. 36A with suture 94 routed through each opening 744 in an alternating or interwoven pattern. Similarly, Fig. 37B shows the ribbon 752 of Fig. 36B with suture 94 routed through openings 754 likewise in an alternating or interwoven pattern. In either case, a terminal end of suture 94 may be formed into a knot 760 distally of the ribbon to prevent the passage of suture 94 proximally. This may be done to facilitate the collapse of the ribbon by simply pulling or tensioning suture 94 to collapse the ribbon upon itself. Rather than forming a knot 760, suture 94 may be attached to the ribbon through any variety of methods, e.g., suture 94 may be tied or welded to the ribbon, or it may simply be attached via an adhesive, etc. Accordingly, when the ribbon is compressed in a longitudinal direction relative to suture 94 by tensioning suture 94, the ribbon compresses into an expanded pattern while bending or folding along the regions in-between the openings.

20

25

30

[0211] Various methods may be utilized to facilitate the bending or folding of the ribbon anchor into desired expanded patterns. One variation may include an elongate ribbon 770 having alternating portions 772 of the ribbon material between the openings 744 notched out or removed, as shown in the variation of Fig. 38. Alternatively, Fig. 39 shows another variation in which the ribbon 780 may be formed to define undulations 782 such that an "S"-type ribbon pattern is fabricated.

[0212] Once the ribbon anchor is urged into its collapsed and deployed configuration, the ribbon anchor may be further configured to provide some degree of spring force which permits the anchor to absorb a range of deflections which may be imparted upon the anchor. The ability of the ribbon anchor to absorb a range of deflections may allow the ribbon anchor to absorb some force which would otherwise be imparted to the underlying tissue surface.

[0213] Such a spring force may be imparted to the ribbon anchor in one variation as shown in Fig. 40A, which shows a perspective view of ribbon anchor 790 with suture 94 routed through the openings. Biasing elements, such as springs 792, may be positioned along portions of ribbon anchor 790 with suture 94 routed therethrough. The variation shows two springs 792 positioned near either end of ribbon 790; however, a single spring or multiple springs may be utilized depending upon the desired elastic spring effects of the ribbon anchor 790. Moreover, the spring or springs 792 may be positioned at any position along the length of the ribbon anchor 790; alternatively, one or more springs 792 may even be positioned proximally or distally of one or both ends of the ribbon anchor 790 rather than between the folds of the ribbon anchor 790.

[0214] Fig. 40B shows a variation in ribbon anchor 790 which is similar to the assembly of Fig. 40A. This variation utilizes biased elements 794, which may be fabricated from one of a variety of metallic or polymeric materials similar to or the same as the material of ribbon anchor 790. Biased elements 794 may generally comprise angled members having suture 94 routed therethrough and which are biased to pivot about a hinge and retain its angled configuration.

[0215] In use, when suture 94 is tensioned or pulled relative to ribbon anchor 790, ribbon anchor 790 may reconfigure itself into its compressed configuration. Fig. 40C shows a perspective view of the ribbon 790 of Fig. 40A which has been partially collapsed. As shown, springs 792 may be compressed between the portions of ribbon anchor 790 and function to provide a biasing force which allows the anchor assembly to absorb a range of

deflections while isolating the force from the underlying tissue. Fig. 40D shows the partially compressed anchor ribbon 790 with the biased elements 794 from Fig. 40B. This variation of the anchor assembly may function similarly to that of the assembly of Fig. 40C.

[0216] An alternative variation of the ribbon anchor is shown in the perspective view of Fig. 41. Rather than utilizing a ribbon or flattened wire, this variation utilizes a tubular member 800 with suture 94 routed through a plurality of openings defined along its length. The tubular member 800 may be fabricated from any of the materials as described above, and because of its circular cross-section, it may provide some spring force as tubular member 800 is collapsed upon itself. Other alternatives may also utilize elongate members having
5 10 elliptical, rectangular, triangular, etc., cross-sections.

[0217] Fig. 42 shows a perspective view of tubular member 810 having a partial cut-out 812 along the length of tubular member 810. A single cut-out may be utilized to provide for a bending portion. Alternatively, multiple cut-outs 822 may be formed in a tubular member 820, as shown in Fig. 43. Multiple cut-outs 822 may be formed along a single side of tubular member 820, or they may be alternated on opposing sides, as shown in the figure. In either
15 case, suture 94 may be routed in an alternating pattern along the lengths of the tubular members to facilitate the bending or folding of the members, as described above.

[0218] Another alternative ribbon anchor 830 is shown in Fig. 44, which illustrates multiple individual lengths of elements 832 encased (or at least partially encased) in a coating or covering 836. Each or a number of the elements 832 may be fabricated from a variety of
20 materials, e.g., metals such as Titanium, stainless steel, Nitinol, etc., or plastics, etc., and the coating or covering 836 may be made from a variety of flexible polymeric or elastomeric materials. The length of the coating or covering 836 extending between each of the elements 832 may function as living hinges 834 while suture 94 may be routed through each or several
25 of the elements 832. When ribbon anchor 830 is compressed, it may fold along the living hinges 834 as described above.

[0219] Fig. 45 shows yet another alternative in which ribbon anchor 840 may be comprised of one or more lengths of wire 842 covered or coated with the same or similar material as coating or covering 836 above. Wires 842 may be fabricated from the same or similar
30 material as elements 832 above. Similarly, suture 94 may be routed through a plurality of openings defined along the length of ribbon anchor 840.

[0220] Fig. 46 shows yet another variation of ribbon anchor 850 which is similar to the ribbon anchors described above, yet this variation may have a length which has a non-uniform thickness. For instance, ribbon anchor 850 may have one or more regions 852 which are notched out or thinned relative to the rest of the length of ribbon anchor 850. The thicknesses of the notched or thinned regions 852 may be varied to alter the bending or folding characteristics of ribbon anchor 850, as desired.

[0221] Fig. 47A shows yet another variation in which a length of wire 860 may simply be utilized to fold or flatten in an expanded pattern. Wire 860 may be extruded from various materials, e.g., stainless steel, Nitinol, Titanium, plastic, etc., and it may be further configured to have shape memory characteristics such that when collapsed, wire 860 folds or collapses into a predetermined pattern. Wire 860 may also comprise one or more eyelets 862 along its length through which suture 94 may be routed. Eyelets 862 may be welded or adhered to wire 860 through any number of fastening methods. Another alternative is shown in Fig. 47B, which is similar to the variation of Fig. 47A. In this variation, a single wire 860', similar to above, may be configured to define a plurality of loops 862' rather than having separate eyelets attached thereto. Suture 94 may be routed through these formed loops 862'.

[0222] Alternatively, a length of wire 870 may be utilized without suture. Fig. 48 shows an example in which wire or ribbon 870 may be comprised of a shape memory alloy, such as Nitinol, which is configured to form a tangled portion 872 of wire 870 when unconstrained, similar to a "bird's nest". This tangled portion 872 may simply expand into an intertwined mass of wire which prevents its passage through a tissue fold F.

[0223] In operation for any of the ribbon anchors described above, one or more ribbon anchors may be utilized. For instance, a first anchor may be positioned distally of a tissue fold F and a second anchor may be positioned proximally of the same tissue fold F, as shown in Fig. 49A. The distal portion of suture 94, which extends between the two anchors, may be anchored to the first anchor via, e.g., fastener or knot 760. As suture 94 is tensioned or pulled, each of the ribbon anchors 742 may be compressed and collapse into an expanded configuration against the tissue fold F. A locking mechanism 880, which may comprise any of the locking mechanisms described above, may be proximally positioned over suture 94 and cinched against the ribbon anchor 742 to thereby lock each of the ribbon anchors 742 into their collapsed and expanded configurations, as shown in Fig. 49B. Although this example illustrates the use of ribbon anchors 742, any of the linear anchors described above may be

utilized either alone or in combination with any other linear anchor or other anchor described above.

[0224] As mentioned above, the ribbon anchor may be collapsed into an expanded configuration against the tissue surface. Accordingly, the ribbon anchor may be configured to collapse in a variety of bowed or expanded configurations such that the contact area of the anchor against the tissue surface is increased, if so desired. Fig. 50A shows a top view of one variation of a ribbon anchor 890 which is configured simply to fold linearly upon itself to form arms 892.

[0225] Fig. 50B shows a top view of another variation 894 in which the ribbon anchor may be configured to form a crossing pattern with at least four arms 896. And Fig. 50C shows a top view of yet another ribbon anchor 898 where multiple arms 900 may be formed in a radial pattern to facilitate the distribution of the anchor against the tissue surface.

[0226] Alternatively, the ribbon anchor may be configured to form a number of secondary support arms 904, as shown in the bowtie-like configuration of variation 902 in Fig. 50D. Fig. 50E shows another variation 906 where a square configuration may be formed via multiple support arms 908 formed by the collapsing anchor. Fig. 50F shows yet another variation 910 where a single support arm 912 may be formed by the collapsing anchor structure. Any number of patterns and folded arms may be formed depending upon the desired configuration and aspects of the collapsed ribbon anchor.

[0227] Referring now to Figs. 51 and 52, a cinching assembly comprising an interference element is described. Cinching assembly 1000 comprises tubular or hollow body member 1002 having distal opening 1004 and proximal opening 1006. If body member 1002 is tubularly or cylindrically shaped, the passage defined through body member 1002 is preferably of a tapered or conical shape. Body member 1002 may optionally be shaped into a tapered or conical configuration. Distal opening 1004 is sized for passage of suture 1008 therethrough, while proximal opening 1006 is sized for passage of both the suture and interference element 1010, illustratively a ball or sphere.

[0228] Assembly 1000 further comprises proximal plug or cap 1012 that is coupled to the proximal end of body member 1002 and that fills proximal opening 1006 of the body member. Plug or cap 1012 may be fitted or held within body member 1002 through a variety of methods. For instance, plug or cap 1012 may be friction-fitted within the proximal opening 1006. Alternatively, plug or cap 1012 may be fitted via a circumferential detent

configured to snap into place within the proximal opening **1006**; and in yet another example, plug or cap **1012** may simply be held within or adjacent to proximal opening **1006** via an adhesive. As best seen in Figs. 52, plug **1012** comprises through-hole **1014** configured for passage of suture **1008** (for the purposes of illustration, suture **1008** is not shown in Figs. 52).

5 [0229] Ball **1010** may, for example, have a diameter between about 0.020" and 0.040", although any other diameter may be provided as desired. Furthermore, the ball may be fabricated from any of a variety of materials, such as aluminum, titanium or steel; alternative materials will be apparent. Suture **1008** may, for example, have a nominal diameter of about 0.016", although other diameters may be provided. Distal opening **1004** of body member
10 **1002** and through-hole **1014** of proximal plug **1012** may, for example, have a diameter of about 0.018", although other diameters may be provided.

[0230] As illustrated by arrows in Figs. 51A, urging body member **1002** distally, i.e., in the direction of the arrows shown, relative to suture **1008** urges ball **1010** towards the proximal end of body member **1002** and against plug or cap **1012**. In this example, since the proximal
15 end of the conical body member may have a larger cross-section than its tapered distal end, suture **1008** may pass freely through cinching assembly **1000**, thereby allowing the suture to be cinched. As illustrated by arrows in Fig. 51B, moving body member **1002** proximally relative to suture **1008** urges ball **1010** towards the tapered distal end of body member **1002**. This interference or friction locks suture **1008** between ball **1010** and the interior wall of
20 body member **1002**, thereby allowing uni-directional cinching of assembly **1000** relative to suture **1008** by locking cinching assembly **1000** and preventing any reverse movement of suture cinching.

[0231] Referring now to Figs. 53, variations of cinching assembly **1000** are described. In the variation of Fig. 53A, conical body **1002** has been replaced with tubular body **1020**
25 having tapered or profiled interior lumen **1021**, which facilitates friction locking of suture **1008** between ball **1010** and the profiled wall of the lumen. Body **1020** may, for example, be machined, cast or molded to achieve the profile of lumen **1021**. Proximal plug **1012** illustratively comprises a hypotube concentrically disposed within body **1020**. Through-hole or lumen **1014** of plug or hypotube **1012** is sized for passage of suture **1008** therethrough, but
30 is smaller than the diameter of ball **1010** to prevent ball **1010** from exiting or falling out of body **1020**.

[0232] Fig. 53B provides a similar variation of assembly 1000 having body 1020' with profiled interior lumen 1021'. In contrast to the variation of Fig. 53A, body 1020' may, for example, comprise a standard hypotube, while the profile of lumen 1021' may be formed via secondary insert 1022 disposed within the hypotube. Insert 1022 may, for example, comprise epoxy injected within the hypotube, or may comprise a separate piece that is friction fit or otherwise fit within the hypotube.

[0233] In the variation of Fig. 53C, assembly 1000 comprises tubular body 1030 having lumen 1031, as well as end cap or plug 1032 with proximal opening 1034 for passage of suture 1008. The end cap may, for example, comprise a bead of epoxy, while the tubular body may comprise a hypotube. Crimped hypotube 1040 is concentrically disposed over or within tubular body 1030 and is coupled to body 1030 at attachment 1042. Attachment 1042 may, for example, comprise a weld formed between the tubular body and the hypotube, or may comprise a glue attachment, such as a cyanoacrylate attachment, etc. Hypotube 1040 further comprises central crimp 1044. The reduced diameter of lumen 1041 through hypotube 1040 in the vicinity of crimp 1044 facilitates friction locking of ball 1010 with suture 1008 to prevent reversal of suture cinching.

[0234] In the variation of Fig. 53D, cinching assembly 1000 is formed from three tubes, e.g., hypotubes. Proximal hypotube 1060 is concentrically disposed within a proximal end of body hypotube 1050, while distal hypotube 1070 is disposed within a distal end of the body hypotube. Body hypotube 1050 comprises lumen 1051 configured for passage of ball 1010 and suture 1008 therethrough; while proximal hypotube 1060 comprises lumen 1061, and distal hypotube 1070 comprises lumen 1071, both of which are configured for passage of suture 1008 therethrough, but not for passage of ball 1010. Body hypotube 1050 and distal hypotube 1070 comprise crimp 1080 that locally reduces lumens 1051 and 1071. As seen in Fig. 53D, the ball and suture are disposed within lumen 1051 in a manner that allows free proximal movement of suture 1008 relative to cinching assembly 1000, but that friction locks suture 1008 between ball 1010 and crimp 880 during distal movement of the suture relative to the assembly.

[0235] The cinching assembly variations of Figs. 51-53 rely on an interference fit and/or friction between a suture, thread or other flexible element; an interference element, such as a ball or sphere; and an interior surface of a body member element through which the flexible element and the interference element pass. The material characteristics and/or surface texture

or roughness of these three elements may be specified to achieve, for example, desired frictional characteristics and interactions, ease of cinch, locking forces, etc. Exemplary materials and surface characteristics for any or all of the cinching assembly elements include, but are not limited to, metals, polymers, elastomers, sandblasted metals, smooth metals, sapphire, glass, etc. Additional materials and surface characteristics will be apparent to those of skill in the art.

[0236] Although a number of illustrative variations are described above, it will be apparent to those skilled in the art that various changes and modifications may be made thereto without departing from the scope of the invention. Moreover, although specific locking or cinching configurations may be shown with various types of anchors, it is intended that the various locking or cinching configurations be utilized with the various types of anchors in various combinations as practicable. It is intended in the appended claims to cover all such changes and modifications that fall within the true spirit and scope of the invention.

WHAT IS CLAIMED IS:

- 1 1. An anchor for implantation in a body, comprising:
2 an anchor body adapted to be delivered through a hollow member for
3 placement against a tissue surface; and
4 a locking mechanism adapted to pass the anchor body in a first direction
5 relative to a flexible member upon application of a cinching force,
6 wherein the locking mechanism is further adapted to impart a locking force
7 upon the flexible member when the anchor body is urged in a second direction opposite to the
8 first direction, and wherein the locking force is greater than the cinching force.
- 1 2. The anchor of claim 1 wherein the anchor body comprises a T-anchor.
- 1 3. The anchor of claim 2 wherein the T-anchor has a cross-sectional
2 shape selected from the group consisting of circles, rectangles, and squares.
- 1 4. The anchor of claim 1 wherein the anchor body comprises a basket
2 anchor.
- 1 5. The anchor of claim 4 wherein the basket anchor is reconfigurable
2 from a delivery configuration within the hollow member to an expanded configuration
3 outside the hollow member.
- 1 6. The anchor of claim 1 wherein the hollow member is selected from the
2 group consisting of tubular members, catheters, needles, and trocars.
- 1 7. The anchor of claim 1 wherein the flexible member comprises a length
2 of suture.
- 1 8. The anchor of claim 7 wherein the suture comprises a plurality of knots
2 or protrusions along the length of the suture.
- 1 9. The anchor of claim 8 wherein the knots or protrusions are formed at
2 regular intervals along the length.
- 1 10. The anchor of claim 8 wherein the knots or protrusions are formed
2 intermittently along the length.

- 1 11. The anchor of claim 7 wherein the length of suture comprises a
2 monofilament, multifilament, elastic, or elastomeric material.
- 1 12. The anchor of claim 7 wherein the length of suture comprises a
2 metallic material.
- 1 13. The anchor of claim 12 wherein the metallic material is selected from
2 the group consisting of Nitinol, stainless steel, and Titanium.
- 1 14. The anchor of claim 7 wherein at least a portion of the length of suture
2 is surrounded by a material having a frictional coefficient higher than the suture.
- 1 15. The anchor of claim 14 wherein the material comprises a metal coating
2 or sleeve.
- 1 16. The anchor of claim 1 wherein the anchor body defines a tapered
2 opening for passage of the flexible member therethrough.
- 1 17. The anchor of claim 1 wherein the locking mechanism comprises at
2 least one biased lever adjacent to an opening defined in the anchor body.
- 1 18. The anchor of claim 1 wherein the locking mechanism is contained
2 within the anchor body.
- 1 19. The anchor of claim 1 wherein the locking mechanism is in-line with
2 the flexible member.
- 1 20. The anchor of claim 1 wherein the locking mechanism is adapted to
2 automatically impart the locking force upon the flexible member.
- 1 21. The anchor of claim 1 wherein the locking mechanism comprises at
2 least one tab biased to cinch against a portion of the flexible member passed through the
3 anchor body.
- 1 22. The anchor of claim 21 wherein the locking mechanism further
2 comprises a tapered member defining a lumen for passage of the flexible member
3 therethrough, the tapered member being adapted to be advanced into the anchor body for
4 releasing the flexible member when the tapered member is positioned against the tab.

1 23. The anchor of claim 1 wherein the locking mechanism comprises at
2 least one arm biased to project into a lumen defined through the anchor body and to cinch the
3 flexible member against a surface of the lumen.

1 24. The anchor of claim 23 wherein the arm is further adapted to release
2 the flexible member when the anchor body is advanced distally.

1 25. The anchor of claim 1 wherein the locking mechanism comprises at
2 least one arm biased to project at an angle proximally of the anchor body.

1 26. The anchor of claim 25 wherein the arm defines a tapered opening
2 through which the flexible member is passed.

1 27. The anchor of claim 25 wherein the arm is integral with the anchor
2 body.

1 28. The anchor of claim 1 wherein the locking mechanism comprises a
2 sleeve which defines a tortuous passageway for passage of the flexible member therethrough.

1 29. The anchor of claim 28 wherein the sleeve is located proximally of the
2 anchor body.

1 30. The anchor of claim 28 wherein the sleeve is integral with the anchor
2 body.

1 31. The anchor of claim 28 wherein the tortuous passageway is defined by
2 at least one obstruction integral with the sleeve such that the obstruction protrudes into a
3 lumen of the sleeve.

1 32. The anchor of claim 31 wherein the at least one obstruction comprises
2 a lever adapted to protrude partially into the lumen.

1 33. The anchor of claim 1 wherein the locking mechanism comprises a
2 sleeve adapted to reconfigure into a crimped configuration.

1 34. A method for cinching an anchor relative to tissue, comprising:
2 ejecting an anchor body from a hollow member in proximity to the tissue;

3 urging the anchor body distally along a flexible member into contact against a
4 surface of the tissue to be cinched; and

5 locking the anchor body with a self-locking mechanism adapted to allow the
6 anchor body to pass distally over the suture while preventing the anchor body from moving
7 proximally over the flexible member.

1 35. The method of claim 34 wherein ejecting an anchor body comprises
2 urging the anchor body from an opening defined at a distal end of the hollow member.

1 36. The method of claim 34 wherein urging the anchor body distally
2 comprises pushing the anchor body via the hollow member.

1 37. The method of claim 34 wherein urging the anchor body distally
2 comprises pushing the anchor body via an elongate push rod.

1 38. The method of claim 34 wherein urging the anchor body distally
2 comprises urging the anchor body along a length of suture.

1 39. The method of claim 34 wherein locking the anchor body with a self-
2 locking mechanism comprises inhibiting proximal movement of the anchor body over the
3 flexible member via at least one biased lever adjacent to an opening defined in the anchor
4 body.

1 40. The method of claim 34 wherein locking the anchor body with a self-
2 locking mechanism comprises advancing a collet into the anchor body to cinch a plurality of
3 locking arms at a distal end of the collet onto the flexible member.

1 41. The method of claim 34 wherein locking the anchor body with a self-
2 locking mechanism comprises cinching the flexible member against a portion of the anchor
3 body via at least one biased tab.

1 42. The method of claim 34 wherein locking the anchor body with a self-
2 locking mechanism comprises cinching the flexible member within an opening defined
3 through at least one biased arm.

1 43. The method of claim 34 wherein locking the anchor body with a self-
2 locking mechanism comprises cinching the flexible member within an opening defined
3 through at least one arm biased to project at an angle proximally of the anchor body.

1 44. The method of claim 34 wherein locking the anchor body with a self-
2 locking mechanism comprises passing the flexible member through a tortuous passageway
3 proximally of the anchor body.

1 45. An anchor for implantation in a body, comprising:
2 an anchor body adapted to be delivered through a hollow member for
3 placement against a tissue surface; and
4 a locking mechanism defining a lumen for passage of a flexible member
5 therethrough,
6 wherein the locking mechanism is positioned proximally of the anchor body
7 and has at least one arm biased to project into the lumen for contact against the flexible
8 member such that the flexible member is uni-directionally advanceable through the lumen
9 relative to the anchor body.

1 46. A method for cinching an anchor relative to tissue, comprising:
2 ejecting an anchor body from a hollow member in proximity to the tissue;
3 urging the anchor body distally along a flexible member into contact against a
4 surface of the tissue to be cinched; and
5 locking the anchor body with a locking mechanism having at least one arm
6 biased to project into a lumen defined by the locking mechanism such that the at least one
7 arm contacts the flexible member and inhibits proximal movement of the anchor body along
8 the flexible member.

1 47. The method of claim 46 wherein ejecting an anchor body comprises
2 urging the anchor body from an opening defined at a distal end of the hollow member.

1 48. The method of claim 46 wherein urging the anchor body distally
2 comprises pushing the anchor body via the hollow member.

1 49. The method of claim 46 wherein urging the anchor body distally
2 comprises pushing the anchor body via an elongate push rod.

1 50. The method of claim 46 wherein urging the anchor body distally
2 comprises urging the anchor body along a length of suture.

1 51. The method of claim 46 wherein locking the anchor body with a
2 locking mechanism comprises cinching the flexible member within an opening defined
3 through at least one arm biased to project at an angle relative to the anchor body.

1 52. The method of claim 46 wherein locking the anchor body with a
2 locking mechanism comprises passing the flexible member through a plurality of additional
3 arms each biased to project at an angle relative to the anchor body, each of the arms
4 positioned in approximation.

1 53. An anchor system for implantation in a body, comprising:
2 an anchor body adapted to be delivered through a delivery device for
3 placement against a tissue surface; and
4 a locking mechanism defining a lumen for passage of a flexible member
5 therethrough,
6 wherein the locking mechanism has an interference element disposed within
7 the lumen that is configured to contact the flexible member, such that the flexible member is
8 uni-directionally advanceable through the lumen relative to the anchor body.

1 54. The anchor system of claim 53, wherein the anchor body comprises a
2 basket anchor.

1 55. The anchor system of claim 53, wherein the anchor body is
2 reconfigurable from a delivery configuration within the delivery device to an expanded
3 configuration outside the delivery device.

1 56. The anchor system of claim 53, wherein the delivery device is selected
2 from the group consisting of endoscopes, hollow members, tubular members, catheters,
3 needles, and trocars.

1 57. The anchor system of claim 53, wherein the flexible member
2 comprises a length of suture.

1 58. The anchor system of claim 53, wherein the locking mechanism is
2 positioned proximally of the anchor body.

1 59. The anchor system of claim 53, wherein the lumen defines a profile
2 configured for passage of the flexible member past the interference element when the anchor
3 body is advanced distally relative to the flexible member.

1 60. The anchor system of claim 53, wherein the lumen defines a profile
2 configured to preclude passage of the flexible member past the interference element when the
3 anchor body is moved proximally relative to the flexible member.

1 61. The anchor system of claim 60, wherein the locking mechanism is
2 configured to friction lock or interference fit the flexible member between the interference
3 element and a wall of the lumen when the anchor body is moved proximally relative to the
4 flexible member.

1 62. The anchor system of claim 53, wherein the interference element
2 comprises a ball or sphere.

1 63. The anchor system of claim 53, wherein the interference element is
2 adapted to cinch the flexible member against a surface of the lumen.

1 64. A method for securing tissue, comprising:
2 ejecting an anchor body from a delivery device in proximity to the tissue;
3 urging the anchor body distally along a flexible member into contact against a
4 surface of the tissue to be secured; and
5 locking the anchor body with a locking mechanism having an interference
6 element disposed within a lumen defined by the locking mechanism, such that the
7 interference element contacts the flexible member and inhibits proximal movement of the
8 anchor body along the flexible member.

1 65. The method of claim 64, wherein ejecting an anchor body comprises
2 urging the anchor body from an opening defined at a distal end of the delivery device.

1 66. The method of claim 64, wherein urging the anchor body distally
2 comprises pushing the anchor body via the delivery device or an elongate push rod.

1 67. The method of claim 64, wherein urging the anchor body distally along
2 a flexible member comprises urging the anchor body along a length of suture.

1 68. The method of claim 64, wherein urging the anchor body distally
2 further comprises positioning the interference element within the lumen of the locking
3 mechanism in a manner that facilitates passage of the flexible member past the interference
4 element as the anchor body is urged distally.

1 69. The method of claim 64, wherein locking the anchor body with a
2 locking mechanism further comprises precluding passage of the flexible member past the
3 interference element in a manner that inhibits proximal movement of the anchor body.

1 70. The method of claim 69, wherein precluding passage of the flexible
2 member past the interference element comprises friction locking or interference fitting the
3 flexible member between the interference element and a wall of the locking mechanism
4 lumen when the anchor body is moved proximally along the flexible member.

1/50




FIG. 1A




FIG. 1B




FIG. 1C

2/50




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B

4/50




FIG. 3C







FIG. 3D

5/50



6/50



7/50




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6

8/50




FIG. 7




FIG. 8A




FIG. 8B

9/50




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 9C

10/50




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C

11/50




FIG. 12A




FIG. 12B

12/50




FIG. 12C




FIG. 12D

13/50




FIG. 12E




FIG. 12F




FIG. 12G

14/50




FIG. 13A




FIG. 13B

15/50




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15C




FIG. 15B




FIG. 15D

16/50




FIG. 15E




FIG. 15F




FIG. 15G




FIG. 15H

17/50





FIG. 17A




FIG. 17B

18/50




FIG. 18A




FIG. 18B



FIG. 18C




FIG. 18D




FIG. 19A




FIG. 19B

19/50




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D

20/50




FIG. 20E




FIG. 20F

21/50




FIG. 21A

FIG. 21B




FIG. 22A

22/50




FIG. 22B




FIG. 22C




FIG. 22D




FIG. 22E

23/50




FIG. 23




FIG. 24A

24/50




FIG. 24B




FIG. 24C




FIG. 24D

25/50




FIG. 25A




FIG. 25B




FIG. 25C

26/50




FIG. 26A




FIG. 26B




FIG. 26C




FIG. 26D

27/50




FIG. 26E




FIG. 26F




FIG. 26G

28/50




FIG. 27A




FIG. 27B

29/50

600




FIG. 28A




FIG. 28B




FIG. 28C




FIG. 28D




FIG. 28E

30/50




FIG. 28F

31/50




FIG. 28G




FIG. 28H

32/50




FIG. 29A




FIG. 29B




FIG. 30A




FIG. 30B

33/50




FIG. 31A




FIG. 31B




FIG. 31C








FIG. 31D

34/50



35/50




FIG. 34A




FIG. 34B

36/50




FIG. 35A




FIG. 35B




FIG. 35C




FIG. 35D




FIG. 35E

37/50




FIG. 36A




FIG. 36B

38/50




FIG. 37A




FIG. 37B

39/50




FIG. 38




FIG. 39

40/50




FIG. 40A




FIG. 40B

41/50




FIG. 40C







FIG. 40D

42/50



43/50




FIG. 44







FIG. 45

44/50



45/50




FIG. 48

46/50




FIG. 49A




FIG. 49B

47/50




FIG. 50A




FIG. 50B




FIG. 50C

48/50




FIG. 50D




FIG. 50E




FIG. 50F

49/50




FIG. 51A




FIG. 51B




FIG. 53A




FIG. 53B




FIG. 53C




FIG. 53D

50/50




FIG. 52A




FIG. 52B




FIG. 52C

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US05/15765

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A61B 17/04
US CL : 606/151

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
U.S. : 606/151

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
Please See Continuation Sheet

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6,692,506 B1 (ORY et al) 17 February 2004 (17.02.2004), column 2, lines 32-63.	1-70
Y	US 6,152,935 A (KAMMERER et al) 28 November 2000 (28.11.2000), column 2, lines 53-67.	1-70
Y	US 4,006,747 A (KRONENTHAL et al) 08 February 1977 (08.02.1977), column 1, lines 39-64.	1-70

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"Z" document member of the same patent family

Date of the actual completion of the international search

08 August 2005 (08.08.2005)

Date of mailing of the international search report

13 OCT 2005

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US

Commissioner for Patents

P.O. Box 1450

Alexandria, Virginia 22313-1450

Facsimile No. (703) 305-3230

Authorized officer

Gary Jackson

Telephone No. (703) 308-0858

Sheila L. Vener
Paralegal Specialist
Tech. Center 3700

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US05/15765

Continuation of B. FIELDS SEARCHED Item 3:
606/151
key word: t-shaped fastener